StarTech.com DK30C2DAGPD kannettavien tietokoneiden telakka ja porttitoistin Langallinen USB 3.2 Gen 1 (3.1 Gen 1) Type-C musta

Tuotemerkki : StarTech.com

Tuotekoodi: DK30C2DAGPD

Tuotteen nimi : DK30C2DAGPD

StarTech.com DK30C2DAGPD. Yhteysteknologia: Langallinen, Isäntäkoneen käyttöliittymä: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, USB Power Delivery asti: 100 W. Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s, Verkkostandardit: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u. Tuotteen väri: musta, Tiedonsiirtonopeus: 5 Gbit/s, Digitaalinen enimmäistarkkuus: 4096 x 2160 pikseliä. Virtalähteen malli: USB, Virtalähde: 100 W, Virrankulutus: 15 W. Windows-käyttöjärjestelmätuki: Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10...

Ports & interfaces

Connectivity technology *	Wired
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB 2.0 ports quantity *	1
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	1
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1
USB Power Delivery (USB PD)	✔
USB Power Delivery revision	3.0
USB Power Delivery up to	100 W
DisplayPorts quantity	2
Microphone in *	✘

Network

Ethernet LAN *	✔
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	10,100,1000 Mbit/s
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u
Auto MDI/MDI-X	✔
Full duplex	✔
10G support	✘

Performance

Card reader integrated *	✘
Data transfer rate	5 Gbit/s
Maximum digital resolution	4096 x 2160 pixels
Product colour *	Black
UASP support	✔
Housing material	Plastic

Power

Power consumption (typical)	15 W

Software

Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64

Operational conditions

Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	0 - 95%

Weight & dimensions

Width	60 mm
Depth	120 mm

Performance	
Brand compatibility	Any brand
Certification	CE, FCC, REACH

Power	
Power source type	USB
Power supply	100 W

Weight & dimensions	
Height	18.8 mm
Weight	150 g

Packaging data	
Package width	145 mm
Package depth	208 mm
Package height	42 mm
Package weight	300 g

Packaging content	
Cables included	USB Type-C
Quick start guide	✔

Technical details	
Compliance certificates	RoHS

Logistics data	
Products per master (outer) case	24 pc(s)
Master (outer) case width	310 mm
Master (outer) case length	450 mm
Master (outer) case height	280 mm
Harmonized System (HS) code	84733020

Other features	
Chipset	VIA/VLI - VL102, VIA/VLI - VL170, VIA/VLI - VL817, MegaChips - STDP4320, RealTek - RTL8153

0065030878746

065030878746

Publication date: 26-DEC-2024. Prints or copies of Information are only valid on the printed Publication date