
QNAP

QNAP TS-h2490FU NAS Teline (2U) EPYC 7232P 64 GB DDR4 0 TB QuTS hero musta, Harmaa

Tuotemerkki: QNAP Tuotekoodi: TS-H2490FU-7232P-64G

Tuotteen nimi: TS-h2490FU







Storage		Design	
Storage drive capacity * 0 GB	LED indicators	HDD, LAN, Status	
	U.2	Performance	
Storage drives installed * Total installed storage capacity *	2.5" v 0, 1, 5, 6, 10, 50, 60 v FAT32, HFS+, NTFS, ZFS, ext3, ext4 X 0 TB 24	Type * Device class * Backup function * Backup features Buzzer Multilingual support Noise level Snapshot Web-based management Security algorithms Access Control List (ACL) Reset button	NAS Large Enterprise Business Cloud, iSCSI LUN 53.5 dB 256-bit AES, HTTPS, SSH, SSL/TLS
Supported storage drive types *	SSD	On/off switch	✓
Bad block scan	✓	Built-in FTP server	✓
Processor Processor manufacturer * AMD Processor family * EPYC Processor model * 7232P Processor frequency * 3.1 GHz Processor boost frequency 3.2 GHz Processor cores 8	Browser supported System log Hot spare S.M.A.R.T. support Universal Plug and Play (UPnP)	Mozilla Firefox, Microsoft Internet Explorer, Apple Safari, Google Chrome	
Processor threads	16	Software	
L3 cache	32 MB	Operating system installed * QuTS hero	QuTS hero h5.0.0
Memory		Operating system version	0.0.0
Internal memory * Internal memory type Maximum RAM supported Memory slots Memory form factor ECC Flash memory	64 GB DDR4 4 TB 16 RDIMM * 5000 MB		

Network		Software	
Ethernet LAN *	✓		Windows 10, Windows 10
Ethernet LAN data rates DHCP client DHCP server Jumbo frames support iSCSI support Wake-on-LAN ready Supported network protocols Link aggregation Load balancing system Dynamic DNS (DDNS) WLAN adapter supported Ports & interfaces	10,100,1000,2500,25000 Mbit/s	Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise,
USB port *	✓		Windows 8 Enterprise x64, Windows 8 Pro Windows 8 Pro x64, Windows
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity Fiber ports quantity Fiber optic connector Ethernet LAN (RJ-45) ports * Concurrent connections	2 SFP28 2 10000	Linux operating systems supported	8 Pro, Windows 8 Pro x64, Windows 8 x64 CentOS 7.0, SuSE Linux 12.0, SuSE Linux 12.3, SuSE Linux 15, Ubuntu 14.04, Ubuntu 14.10, Ubuntu 15.04, Ubuntu 15.10, Ubuntu 16.04, Ubuntu 16.10, Ubuntu 17.10, Ubuntu 18.04 LTS, Ubuntu 20.04 LTS
Design	D. 1 (211)		Mac OS X 10.10 Yosemite, Mac OS X
Chassis type * Cooling type * Product colour Number of fans Fan diameter	Rack (2U) Active Black, Grey 4 fan(s) 6 cm	Mac operating systems supported	10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur
		Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server
		Other operating systems supported	IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11
		Power	
		Power supply location Power supply unit (PSU) capacity Number of power supply units Power consumption (typical) AC input voltage Fan voltage	Built-in 1100 W 2 277.64 W 100 - 240 V 12 V
		Weight & dimensions	
		Width * Depth * Height * Weight Package weight	481 mm 510.2 mm 88.3 mm 15.2 kg 21.9 kg
		Packaging content	
		Cables included Power cables quantity Quick installation guide Number of screws	AC, LAN (RJ-45) 2 ✓ 96
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T) Storage relative humidity (H-H)	0 - 40 °C 5 - 95% -20 - 70 °C 5 - 95%

Logistics data	
Harmonized System (HS) code	84714100
Other features	
Fibre Channel	1





4713213518397

0885022020416



885022020416

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.