

Epson EB-W06 Standard throw projector 3700 ANSI lumens 3LCD WXGA (1280x800) White



Brand : Epson

Product code: V11H973040

Product name : EB-W06

- Create the big screen experience: From box sets to business presentations, capture everyone's attention

- Bright even with ambient light: Equally high White and Colour Light Output of 3,700 lumens

- Affordable, high-tech equipment: Enjoy this WXGA projector

- Long-lasting solution: 18 years' worth of entertainment²

- Portable and quick to set up: Easy to position with keystone slider

3LCD, 0.59", WXGA, 1280 x 800, 16:10, 16000 : 1, UHE, 210 W, 327 W, 2.5 kg

Epson EB-W06. Projector brightness: 3700 ANSI lumens, Projection technology: 3LCD, Projector native resolution: WXGA (1280x800). Light source type: Lamp, Service life of light source: 6000 h, Service life of light source (economic mode): 12000 h. Focus: Manual, Focal length range: 16.9 - 20.28 mm, Aperture range (F-F): 1.49 - 1.72. Video colour modes: Blackboard, Cinema, Dynamic, Presentation, sRGB. Noise level: 37 dB, Noise level (economic mode): 28 dB, Country of origin: Philippines

| Projector | | Features | |
|--|---|-----------------------------------|--------------------------|
| Screen size compatibility * | 838.2 - 8128 mm (33 - 320") | Password protection | ✓ |
| Projection distance | 1.68 - 2.02 m | Multimedia | |
| Projector brightness * | 3700 ANSI lumens | Built-in speaker(s) * | ✓ |
| Projection technology * | 3LCD | RMS rated power | 2 W |
| Projector native resolution * | WXGA (1280x800) | Design | |
| Contrast ratio (typical) * | 16000:1 | Market positioning * | Home cinema |
| Native aspect ratio * | 16:10 | Product type * | Standard throw projector |
| Number of colours | 1.07 billion colours | Product colour * | White |
| Projector brightness (economic mode) | 2400 ANSI lumens | Placement | Ceiling, Desktop |
| Vertical scan range | 100 - 120 Hz | Cable lock slot | ✓ |
| Keystone correction, horizontal | -30 - 30° | Cable lock slot type | Kensington |
| Keystone correction, vertical | -30 - 30° | Display | |
| Matrix size | 1.5 cm (0.59") | Built-in display * | ✗ |
| Matrix type | 3-panel (p-Si TFT active) | Power | |
| Light source | | Power source * | AC |
| Light source type * | Lamp | Power consumption (typical) * | 327 W |
| Service life of light source * | 6000 h | Power consumption (standby) * | 0.3 W |
| Service life of light source (economic mode) | 12000 h | Power consumption (economy mode) | 225 W |
| Lamp type | UHE | AC input voltage | 100-240 V |
| Lamp power | 210 W | AC input frequency | 50 - 60 Hz |
| Lens system | | Operational conditions | |
| Focus * | Manual | Operating temperature (T-T) | 5 - 35 °C |
| Focal length range | 16.9 - 20.28 mm | Storage temperature (T-T) | -10 - 60 °C |
| Aperture range (F-F) | 1.49 - 1.72 | Operating relative humidity (H-H) | 20 - 80% |
| Zoom capability | ✓ | Storage relative humidity (H-H) | 10 - 90% |
| Zoom type | Manual | Weight & dimensions | |
| Zoom ratio | 1.2:1 | Width | 302 mm |
| Throw ratio | 1.30 - 1.56:1 | Depth | 237 mm |
| Video | | Height | 82 mm |
| Full HD * | ✗ | Weight * | 2.5 kg |
| 3D * | ✗ | Package width | 335 mm |
| Video colour modes | Blackboard, Cinema, Dynamic, Presentation, sRGB | Package depth | 370 mm |
| Ports & interfaces | | Package height | 150 mm |
| USB 2.0 ports quantity | 1 | Package weight | 3.88 kg |

| Ports & interfaces | | Packaging content | |
|-------------------------------|-------------|-----------------------------|---|
| USB 2.0 Type-B ports quantity | 1 | Remote control included * | ✓ |
| VGA (D-Sub) ports quantity * | 1 | Cables included | AC, VGA |
| HDMI ports quantity * | 1 | Quick start guide | ✓ |
| Composite video in * | 1 | Manual | ✓ |
| DVI port * | ✗ | | |
| Network | | Bundled software | Inhalt DIY-App, EasyMP Multi PC Projection, Epson Projektor Management, Epson Projektor Professional Tool |
| Smart TV * | ✗ | Technical details | |
| Ethernet LAN * | ✗ | USB display function | 2 in 1: Image / Mouse |
| Wi-Fi * | ✗ | Logistics data | |
| Storage | | Quantity per pack | 1 pc(s) |
| Card reader integrated * | ✗ | Products per pallet | 84 pc(s) |
| Features | | Pallet gross weight | 0 g |
| Noise level (economic mode) | 28 dB | Products per pallet (UK) | 84 pc(s) |
| Noise level * | 37 dB | Pallet weight (UK) | 0 g |
| Country of origin | Philippines | Harmonized System (HS) code | 85286200 |



8715946680569

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-FEB-2025. Prints or copies of Information are only valid on the printed Publication date