



APC BX1200MI UPS-virtalähde Linjainteraktiivinen 1,2 kVA 650 W 6 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: BX1200MI

Tuotteen nimi : BX1200MI

APC BX1200MI. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 1,2 kVA, Lähtöteho: 650 W. Pistorasian tyypit: C13 liitin, Virtapistoke: C14 liitin, Ulostulojen määrä: 6 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Tyypillinen varmuuskopioaika täydellä kuormituksella: 1 min, Tyypillinen varmuuskopioaika puolikkaalla kuormituksella: 5 min. Kotelo: Kompakti, Tuotteen väri: musta, Johdon pituus: 1,2 m. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: CB Meet EN62040-1 / CE / IEC-62040-1 / IEC-62040-2



| Features | | Battery | |
|--------------------------------------|-------------------|------------------------------------|--|
| UPS topology * | Line-Interactive | Typical backup time at half load | 5 min |
| Output power capacity * | 1.2 kVA | Battery life (max) | 2 year(s) |
| Output power * | 650 W | Battery recharge time | 8 h |
| Waveform * | Sine | Design | |
| Input operation voltage (min) * | 140 V | Form factor * | Compact |
| Input operation voltage (max) * | 300 V | Cable length | 1.2 m |
| Input frequency * | 50/60 Hz | Product colour * | Black |
| Output operation voltage (min) | 230 V | LED indicators | ✓ |
| Output operation voltage (max) | 230 V | International Protection (IP) code | IP20 |
| Output frequency | 50/60 Hz | Operational conditions | |
| Output frequency regulation | 0.5 Hz | Operating temperature (T-T) | 0 - 40 °C |
| Output voltage regulation | 10% | Storage temperature (T-T) | -15 - 40 °C |
| Automatic Voltage Regulation (AVR) ✓ | | Operating relative humidity (H-H) | 0 - 95% |
| Surge energy rating | 273 J | Operating altitude | 0 - 3000 m |
| Response time | 6 ms | Certificates | |
| Input power factor | 0.54 | Compliance certificates | RoHS |
| Noise level | 40 dB | Certification | CB Meet EN62040-1 / CE / IEC-62040-1 / IEC-62040-2 |
| Audible alarm(s) ✓ | | Packaging content | |
| Audible alarm modes | Low battery alarm | Cables included | Input power cable |
| Ports & interfaces | | Manual | ✓ |
| AC outlet types | C13 coupler | Weight & dimensions | |
| Power plug | C14 coupler | Width | 140 mm |
| AC outlets quantity | 6 AC outlet(s) | Depth | 390 mm |
| USB port ✓ | | Height | 190 mm |
| USB 2.0 ports quantity | 1 | Weight | 7.6 kg |
| USB port type | USB Type-B | | |
| Ethernet LAN (RJ-45) ports | 2 | | |

Battery

| | |
|----------------------------------|-------------------------|
| Battery technology | Sealed Lead Acid (VRLA) |
| Typical backup time at full load | 1 min |

Packaging data

| | |
|----------------|--------|
| Package width | 235 mm |
| Package depth | 495 mm |
| Package height | 297 mm |
| Package weight | 8.6 kg |

Logistics data

| | |
|-----------------------------|----------|
| Harmonized System (HS) code | 85078000 |
|-----------------------------|----------|



0731304410812



731304410812

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.