

APC BX1600MI UPS-virtalähde Linjainteraktiivinen 1,6 kVA 900 W 6 AC-pistorasia(a)

Tuotemerkki : APC Tuotekoodi: BX1600MI

Tuotteen nimi: BX1600MI

APC BX1600MI. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 1,6 kVA, Lähtöteho: 900 W. Pistorasian tyypit: C13 liitin, Virtapistoke: C13 liitin, Ulostulojen määrä: 6 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 7 ah, Akun jännite: 24 V. Kotelo: Kompakti, Tuotteen väri: musta, Johdon pituus: 1,2 m. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: CB Meet EN62040-1 / CE / IEC-62040-1 / IEC-62040-2





Features		Battery	
UPS topology * Output power capacity * Output power * Waveform *	Line-Interactive 1.6 kVA 900 W Sine	Typical backup time at full load Typical backup time at half load Battery life (max) Battery recharge time	1 min 6.5 min 2 year(s) 8 h
Input operation voltage (min) *	140 V	Design	
Input operation voltage (max) * Input frequency * Output operation voltage (min) Output operation voltage (max) Output frequency Output frequency regulation Output voltage regulation	300 V 50/60 Hz 230 V 230 V 50/60 Hz 0.5 Hz 10%	Form factor * Cable length Built-in fan Product colour * LED indicators International Protection (IP) code	Compact 1.2 m Black IP20
Automatic Voltage Regulation (AV		Operational conditions	
Surge energy rating Response time Input power factor Noise level	273 J 6 ms 0.56 40 dB	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Operating altitude	0 - 40 °C -15 - 40 °C 0 - 95% 0 - 3000 m
Audible alarm(s)	✓	Certificates	
Audible alarm modes	Low battery alarm	Compliance certificates	RoHS
Ports & interfaces AC outlet types	C13 coupler	Certification	CB Meet EN62040-1 / CE / IEC-62040-1 / IEC-62040-2
Power plug	C13 coupler	Packaging content	
AC outlets quantity USB port	6 AC outlet(s) ✓	Cables included Manual	Input power cable ✓
USB 2.0 ports quantity USB port type	1 USB Type-B	Weight & dimensions	
Ethernet LAN (RJ-45) ports	2	Width Depth	140 mm 390 mm

Battery		Weight & dimensions	
Battery technology	Sealed Lead Acid (VRLA)	Height	190 mm
Battery capacity Battery voltage	7 Ah	Weight	10.3 kg
	24 V	Packaging data	
		Package width	390 mm
		Package depth	140 mm
		Package height	190 mm
		Package weight	11.3 kg
		Logistics data	
		Harmonized System (HS) code	85078000





731304410829

0731304410829

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.