

APC Smart-UPS On-Line, 5kVA, Rackmount 3U, 230V, 6x C13+4x C19 IEC outlets, Network Card+SmartSlot, Extended runtime, W/rail kit, Marine



Brand: APC Product code: SRT5KRMXLIM

Product name : Smart-UPS On-Line, 5kVA, Rackmount 3U, 230V, 6x C13+4x C19 IEC outlets, Network Card+SmartSlot, Extended runtime, W/ rail kit, Marine



Smart-UPS On-Line, 5kVA, Rackmount 3U, 230V, 6x C13+4x C19 IEC outlets, Network Card+SmartSlot, Extended runtime, W/ rail kit, Marine


APC Smart-UPS On-Line, 5kVA, Rackmount 3U, 230V, 6x C13+4x C19 IEC outlets, Network Card+SmartSlot, Extended runtime, W/ rail kit, Marine. UPS topology: Double-conversion (Online), Output power capacity: 5 kVA, Output power: 4500 W. AC outlet types: C13 coupler, C19 coupler, IEC Jumpers, Power plug: Terminal, AC outlets quantity: 12 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 1 h. Form factor: Mini Tower, Product colour: Black, Display type: LCD. Width: 432 mm, Depth: 719 mm, Height: 130 mm

Features		Battery	
UPS topology * Output power capacity * Output power * Waveform * Input operation voltage (min) * Input operation voltage (max) *	but power capacity * 5 kVA 4500 W Pure sine It operation voltage (min) * 160 V It operation voltage (max) * 275 V It frequency * 45/65 Hz But operation voltage (min) 220 V But operation voltage (max) 230 V But operation voltage (max) 230 V But frequency 50/60 Hz But factor 3:1	Number of batteries supported Battery life (max) Battery recharge time Hot-swap battery Automatic battery test	1 5 year(s) 1 h
Input frequency * Output operation voltage (min) Output operation voltage (max) Output frequency Surge energy rating Crest factor Emergency Power Off (EPO)		Posign Form factor * Product colour * Display type LED indicators International Protection (IP) code Certification	Mini Tower Black LCD ✓ IP20 CE, DNV, EAC, RCM, VDE, REACH
Output voltage Total Harmonic Distortion (THD) Noise level Surge protection Audible alarm(s) Temperature voltage compensation	3% 55 dB ✓	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude	0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3000 m
Ports & interfaces		Non-operating altitude	0 - 15000 m
AC outlet types Power plug	C13 coupler, C19 coupler, IEC Jumpers Terminal	Technical details Compliance certificates	RoHS
AC outlets quantity	12 AC outlet(s)	Weight & dimensions	
USB port USB 2.0 ports quantity Serial interface Serial interface type Serial ports quantity Ethernet LAN (RJ-45) ports Cabling technology SmartSlot	1 RJ-45 1 1 10/100Base-T	Width Depth Height Weight Package width Package depth Package height Package weight	432 mm 719 mm 130 mm 54.4 kg 610 mm 960 mm 330 mm 66.9 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Quick installation guide Resource CD Warranty card	

	::	4-4-
LOG	istics	aata

Harmonized System (HS) code

85078000





731304320821

0731304320821

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.