



APC SRT5KRMXLIM UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 5 kVA 4500 W 12 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SRT5KRMXLIM

Tuotteen nimi : SRT5KRMXLIM


APC SRT5KRMXLIM. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 5 kVA, Lähtöteho: 4500 W. Pistorasian tyypit: C13 liitin, C19 liitin, IEC Jumpers, Virtapistoke: Pääte, Ulostulojen määrä: 12 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kestoikä (maks.): 5 vuosi/vuosia, Akun latausaika: 1 h. Kotelo: Mini Tower, Tuotteen väri: musta, Näytön tyyppi: LCD. Tuotteen leveys: 432 mm, Tuotteen syvyys: 719 mm, Tuotteen korkeus: 130 mm



Features		Battery	
UPS topology *	Double-conversion (Online)	Number of batteries supported	1
Output power capacity *	5 kVA	Battery life (max)	5 year(s)
Output power *	4500 W	Battery recharge time	1 h
Waveform *	Pure sine	Hot-swap battery	✓
Input operation voltage (min) *	160 V	Automatic battery test	✓
Input operation voltage (max) *	275 V		
Input frequency *	45/65 Hz		
Output operation voltage (min)	220 V		
Output operation voltage (max)	230 V		
Output frequency	50/60 Hz		
Surge energy rating	480 J		
Crest factor	3:1		
Emergency Power Off (EPO)	✓		
Output voltage Total Harmonic Distortion (THD)	3%		
Noise level	55 dB		
Surge protection	✓		
Audible alarm(s)	✓		
Temperature voltage compensation	✓		
Ports & interfaces		Design	
AC outlet types	C13 coupler, C19 coupler, IEC Jumpers	Form factor *	Mini Tower
Power plug	Terminal	Product colour *	Black
AC outlets quantity	12 AC outlet(s)	Display type	LCD
USB port	✓	LED indicators	✓
USB 2.0 ports quantity	1	International Protection (IP) code	IP20
Serial interface	✓	Certification	CE, DNV, EAC, RCM, VDE, REACH
Serial interface type	RJ-45		
Serial ports quantity	1		
Ethernet LAN (RJ-45) ports	1		
Cabling technology	10/100Base-T		
SmartSlot	✓		
Battery		Operational conditions	
Battery technology	Sealed Lead Acid (VRLA)	Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-15 - 45 °C
		Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
		Technical details	
		Compliance certificates	RoHS
		Weight & dimensions	
		Width	432 mm
		Depth	719 mm
		Height	130 mm
		Weight	54.4 kg
		Package width	610 mm
		Package depth	960 mm
		Package height	330 mm
		Package weight	66.9 kg
		Packaging data	
		Quick installation guide	✓
		Resource CD	✓
		Warranty card	✓
		Logistics data	
		Harmonized System (HS) code	85078000



0731304320821



731304320821

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.