

## APC SRT1000RMXLI UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 1 kVA 1000 W

Tuotemerkki : APC

Tuotekoodi: SRT1000RMXLI

Tuotteen nimi : SRT1000RMXLI

APC SRT1000RMXLI. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 1 kVA, Lähtöteho: 1000 W. Sarjaliitännän tyyppi: RJ-45. Akkuteknologia: Sealed Lead Acid (VRLA), Akun kestoikä (maks.): 5 vuosi/vuosia, Akun latausaika: 3 h. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Johdon pituus: 1,5 m. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: CE, EAC





Features		Design	
UPS topology *Double-conversion (Online)Output power capacity *1 kVAOutput power *1000 WWaveform *SineInput operation voltage (min) *50 VInput operation voltage (max) *150 VInput operation voltage (max) *40/70 HzOutput operation voltage (min)220 VOutput operation voltage (max)440 VOutput operation voltage (max)240 VOutput frequency50/60 HzSurge energy rating432 JCrest factor3:1Emergency Power Off (EPO)✓Noise level50 dBAudible alarm(s)✓	1 kVA 1000 W Sine 50 V 150 V 40/70 Hz 220 V	Cable length Product colour * LED indicators International Protection (IP) code	1.5 m Black Status IP20
		<b>Operational conditions</b> Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C -20 - 50 °C 0 - 95%
	50/60 Hz 432 J	Storage relative humidity (H-H) Certificates Compliance certificates	0 - 95% RoHS
	Certification <b>Sustainability</b> Sustainability certificates	CE, EAC Green Premium	
Ports & interfaces		Weight & dimensions	
USB port USB 2.0 ports quantity Serial interface Serial interface type	✓ 1 ✓ RJ-45	Width Depth Height Weight	432 mm 505 mm 85 mm 21 kg
SmartSlot	✓	Packaging data	
BatterySealed Lead AciaBattery technologySealed Lead AciaBattery life (max)5 year(s)Battery recharge time3 h	, , , ,	Package width Package depth Package height Package weight	594 mm 749 mm 246 mm 29.6 kg
Hot-swap battery	1	Logistics data Products per pallet	12 pc(s)
		Froducts per pallet	12 hc(2)

Design		Logistics data	
Form factor *	Rackmount/Tower	Harmonized System (HS) code	85078000
		Total carbon footprint (kg of CO2e)	1843.14





731304340256

0731304340256

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.