



APC SRT1000RMXLI-NC UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 1 kVA 1000 W

Tuotemerkki : APC

Tuotekoodi: SRT1000RMXLI-NC

Tuotteen nimi : SRT1000RMXLI-NC



APC SRT1000RMXLI-NC. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 1 kVA, Lähtöteho: 1000 W. Sarjaliitännän tyyppi: RJ-45. Akkuteknologia: Sealed Lead Acid (VRLA), Akun jännite: 48 V, Akun kestoikä (maks.): 5 vuosi/vuosia. Kotelo: Telineasennettava, Tuotteen väri: musta, Johdon pituus: 1,5 m. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: CE, EAC



Features		Design	
UPS topology *	Double-conversion (Online)	Cable length	1.5 m
Output power capacity *	1 kVA	Product colour *	Black
Output power *	1000 W	Display type	LCD
Waveform *	Sine	LED indicators	Status
Input operation voltage (min) *	50 V	International Protection (IP) code	IP20
Input operation voltage (max) *	150 V	Operational conditions	
Input frequency *	40/70 Hz	Operating temperature (T-T)	0 - 40 °C
Output operation voltage (min)	220 V	Storage temperature (T-T)	-20 - 50 °C
Output operation voltage (max)	240 V	Operating relative humidity (H-H)	0 - 95%
Output frequency	50/60 Hz	Storage relative humidity (H-H)	0 - 95%
Surge energy rating	432 J	Certificates	
Crest factor	3:1	Compliance certificates	RoHS
Emergency Power Off (EPO)	✓	Certification	CE, EAC
Audible alarm(s)	✓	Sustainability	
Ports & interfaces		Sustainability certificates	Green Premium
USB port	✓	Weight & dimensions	
USB 2.0 ports quantity	1	Width	432 mm
Serial interface	✓	Depth	505 mm
Serial interface type	RJ-45	Height	85 mm
SmartSlot	✓	Weight	21 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Package width	594 mm
Battery voltage	48 V	Package depth	749 mm
Battery life (max)	5 year(s)	Package height	246 mm
Battery recharge time	1 h	Package weight	29.6 kg
Hot-swap battery	✓		

Design


Form factor * Rackmount

Logistics data

Products per pallet	12 pc(s)
Harmonized System (HS) code	85078000
Total carbon footprint (kg of CO2e)	1843.14



0731304340263



731304340263

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.