



APC SRVPM1KIL UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 1 kVA 800 W 3 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SRVPM1KIL

Tuotteen nimi : SRVPM1KIL

APC SRVPM1KIL. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 1 kVA, Lähtöteho: 800 W. Pistorasian tyypit: C13 liitin, Virtapistoke: C14 liitin, Ulostulojen määrä: 3 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun latausaika: 4 h. Kotelo: Tower, Tuotteen väri: musta, Näytön tyyppi: LCD. Tuotteen leveys: 145 mm, Tuotteen syvyys: 288 mm, Tuotteen korkeus: 223 mm




Features		Battery	
UPS topology *	Double-conversion (Online)	Automatic battery test	✓
Output power capacity *	1 kVA	Design	
Output power *	800 W	Form factor *	Tower
Waveform *	Sine	Product colour *	Black
Input operation voltage (min) *	160 V	Display type	LCD
Input operation voltage (max) *	280 V	LED indicators	✓
Input frequency *	40/70 Hz	Certification	CE, IEC 62040-1-1, IEC 62040-1-2 REACH
Output operation voltage (min)	220 V	Operational conditions	
Output operation voltage (max)	240 V	Operating temperature (T-T)	0 - 40 °C
Surge energy rating	600 J	Storage temperature (T-T)	-20 - 50 °C
Crest factor	3:1	Operating relative humidity (H-H)	0 - 95%
ECO mode	✓	Storage relative humidity (H-H)	0 - 95%
Output voltage Total Harmonic Distortion (THD)	3%	Operating altitude	0 - 3000 m
Audible alarm(s)	✓	Non-operating altitude	0 - 14763.6 m
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Technical details	
Auto-restart	✓	Compliance certificates	RoHS
Ports & interfaces		Weight & dimensions	
AC outlet types	C13 coupler	Width	145 mm
Power plug	C14 coupler	Depth	288 mm
AC outlets quantity	3 AC outlet(s)	Height	223 mm
USB port	✓	Weight	9.3 kg
USB 2.0 ports quantity	1	Battery width	23.5 cm
Serial interface	✓	Battery depth	36.5 cm

Ports & interfaces		Weight & dimensions	
Serial interface type	RS-232	Battery height	33 cm
Serial ports quantity	1	Battery weight	10.6 kg
SmartSlot	✓	Packaging data	
Battery		Cables included	USB cable
Battery technology	Sealed Lead Acid (VRLA)	Manual	✓
Battery recharge time	4 h	Logistics data	
		Harmonized System (HS) code	85078000
		Other features	
		Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304343424



731304343424

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.