

APC SRVPM6KIL UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 6 kVA 6000 W

Tuotemerkki : APC Tuotekoodi: SRVPM6KIL

Tuotteen nimi: SRVPM6KIL

APC SRVPM6KIL. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 6 kVA, Lähtöteho: 6000 W. Akun latausaika: 3 h. Kotelo: Tower, Tuotteen väri: musta, Näytön tyyppi: LCD. Tuotteen leveys: 190 mm, Tuotteen syvyys: 374 mm, Tuotteen korkeus: 336 mm. Sisältää johdot: USB-kaapeli





| Features | | Design | |
|---------------------------------|-----------------------------------|-----------------------------------|----------------------------------|
| UPS topology * | Double-conversion (Online) | Product colour * | Black |
| Output power capacity * | 6 kVA | Display type | LCD |
| Output power * | 6000 W | LED indicators | ✓ |
| Waveform * | Sine | Certification | CE, IEC 62040-1-1, IEC 62040-1-2 |
| Input operation voltage (min) * | 220 V | Certification | REACH |
| Input operation voltage (max) * | 240 V | Operational conditions | |
| Input frequency * | 40/70 Hz | Operating temperature (T-T) | 0 - 40 °C |
| Output operation voltage (min) | 220 V | Operating relative humidity (H-H) | 0 - 95% |
| Output operation voltage (max) | 240 V | Storage relative humidity (H-H) | 0 - 95% |
| Surge energy rating | 600 J | Operating altitude | 0 - 3000 m |
| Crest factor | 3:1 | Non-operating altitude | 0 - 14763 m |
| ECO mode | ✓ | Technical details | |
| Emergency Power Off (EPO) | • | Compliance certificates | RoHS |
| Audible alarm(s) | ✓ | • | 1.01.5 |
| Audible alarm modes | Low battery alarm, Overload alarm | Weight & dimensions | |
| Auto-restart | ✓ | Width | 190 mm |
| Ports & interfaces | | Depth | 374 mm |
| USB port | / | Height | 336 mm |
| Serial ports quantity | 1 | Weight | 13 kg |
| | _ | Package width | 290 mm |
| SmartSlot | ✓ | Package depth | 1247 mm |
| Battery | | Package height | 460 mm |
| Battery recharge time | 3 h | Package weight | 16 kg |
| Automatic battery test | ✓ | | |

| Design | | Packaging data | |
|---------------|-------|------------------------|-----------|
| Form factor * | Tower | Cables included | USB cable |
| | | Manual | ✓ |
| | | Other features | |
| | | Nominal output voltage | 230 V |
| | | Nominal input voltage | 230 V |





731304343455

0731304343455

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.