

APC Easy UPS On-Line, 10kVA/10kW, Tower, 230V, 1x Hard wire 3wire(1P+N+E) outlet, Intelligent Card Slot, LCD, Extended runtime, No battery

Brand : APC

Product code: SRVPM10KIL

Product name : Easy UPS On-Line, 10kVA/10kW, Tower, 230V, 1x Hard wire 3-wire(1P+N+E) outlet, Intelligent Card Slot, LCD, Extended runtime, No battery

Easy UPS On-Line, 10kVA/10kW, Tower, 230V, 1x Hard wire 3-wire(1P+N+E) outlet, Intelligent Card Slot, LCD, Extended runtime, No battery

APC Easy UPS On-Line, 10kVA/10kW, Tower, 230V, 1x Hard wire 3-wire(1P+N+E) outlet, Intelligent Card Slot, LCD, Extended runtime, No battery. UPS topology: Double-conversion (Online), Output power capacity: 10 kVA, Output power: 10000 W. USB port type: USB Type-B, Serial interface type: RS-232. Form factor: Tower, Product colour: Black, Cooling type: Active. Width: 190 mm, Depth: 447 mm, Height: 336 mm. Cables included: USB cable






Features		Design	
UPS topology * Output power capacity * Output power * Waveform * Input operation voltage (min) * Input operation voltage (max) * Input frequency * Output operation voltage (min) Output operation voltage (max) Output frequency Output voltage regulation	Stopology *Double-conversion (Online)tput power capacity *10 kVAtput power *10000 Wveform *Sineut operation voltage (min) *220 Vut operation voltage (max) *240 Vut frequency *40/70 Hztput operation voltage (max)240 Vtput frequency50/60 Hztput voltage regulation1%rge energy rating600 Jest factor3:1ergency Power Off (EPO)✓	Form factor * Cooling type Built-in fan Product colour * Display type Certification Operational conditions Operating temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	Tower Active ✓ Black LCD IEC 62040-1-1, IEC 62040-1-2 0 - 40 °C 0 - 95% 0 - 95%
Surge energy rating Crest factor Emergency Power Off (EPO) Surge protection		Operating altitude Non-operating altitude Technical details Compliance certificates	0 - 3000 m 0 - 14763.6 m RoHS
Ports & interfaces USB port USB 2.0 ports quantity USB port type Serial interface Serial interface type Serial ports quantity RS-232 ports	✓ 1 USB Type-B ✓ RS-232 1 1	Weight & dimensionsWidthDepthHeightWeightPackage widthPackage depthPackage heightPackage weight	190 mm 447 mm 336 mm 16.5 kg 290 mm 570 mm 460 mm 19.5 kg

Packaging data

Cables included Manual USB cable





731304343400

0731304343400

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.