



APC SMART-UPS SRT LI-ION 2200VA RM UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 2,2 kVA 1980 W 8 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SRTL2200RMXLI-NC

Tuotteen nimi : SMART-UPS SRT LI-ION 2200VA RM

APC SMART-UPS SRT LI-ION 2200VA RM. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 2,2 kVA, Lähtöteho: 1980 W. Pistorasian tyypit: C13 liitin, C19 liitin, Ulostulojen määrä: 8 AC-pistorasia(a). Akkuteknologia: Litiumioni (Li-Ion), Akun jännite: 48 V, Akun kestoikä (maks.): 10 vuosi/vuosia. Kotelo: Telineasennettava, Tuotteen väri: musta, Hopea, Telineen kapasiteetti: 3U. Sertifiointi: CE, EAC



Features		Design	
UPS topology *	Double-conversion (Online)	Rack capacity	3U
Output power capacity *	2.2 kVA	Cable length	1.83 m
Output power *	1980 W	Product colour *	Black, Silver
Waveform *	Sine	Control type	Buttons
Input operation voltage (min) *	160 V	Display type	LCD
Input operation voltage (max) *	275 V	International Protection (IP) code	IP20
Input frequency *	40 - 70 Hz	Operational conditions	
Output operation voltage (min)	220 V	Operating temperature (T-T)	0 - 40 °C
Output operation voltage (max)	240 V	Storage temperature (T-T)	-20 - 50 °C
Output frequency	50/60 Hz	Operating relative humidity (H-H)	0 - 95%
Surge energy rating	432 J	Certificates	
Crest factor	3:1	Certification	CE, EAC
Output voltage Total Harmonic Distortion (THD)	2%	Packaging content	
Noise level	50 dB	Rack mount kit	✓
Surge protection	✓	Cables included	Output power cable, USB cable
Audible alarm(s)	✓	Manual	✓
Auto shut-off	✓	Quick installation guide	✓
Power source type	AC	Sustainability	
Ports & interfaces		Sustainability certificates	Green Premium
AC outlet types	C13 coupler, C19 coupler	Weight & dimensions	
AC outlets quantity	8 AC outlet(s)	Width	432 mm
Emergency Power Off (EPO) connector	✓	Depth	639 mm
Battery		Height	128 mm
Battery technology	Lithium-Ion (Li-Ion)	Weight	30.5 kg
Battery voltage	48 V	Packaging data	
Battery life (max)	10 year(s)	Package width	870 mm
Battery recharge time	4 h	Package depth	600 mm
Design		Package height	245 mm
Form factor *	Rackmount	Package weight	41.4 kg
		Logistics data	
		Harmonized System (HS) code	85078000
		Other features	
		Bypass	Built-in



0731304347545



731304347545



8592978146061

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.