



APC SRTL1000RMXLI UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 1 kVA 900 W 8 AC-pistorasia(a)



Tuotemerkki : APC

Tuotekoodi: SRTL1000RMXLI


Tuotteen nimi : SRTL1000RMXLI

APC SRTL1000RMXLI. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 1 kVA, Lähtöteho: 900 W. Pistorasian tyypit: C13 liitin, Virtapistoke: C14 liitin, Ulostulojen määrä: 8 AC-pistorasia(a). Akkuteknologia: Litiumioni (Li-Ion), Akun kestoikä (maks.): 10 vuosi/vuosisia, Akun latausaika: 6 h. Kotelo: Telineasennettava, Tuotteen väri: musta, Harmaa, Telineen kapasiteetti: 3U. Sertifiointi: CE, EAC, RCM, VDE

Features		Battery	
UPS topology *	Double-conversion (Online)	Cold start	✓
Output power capacity *	1 kVA	Design	
Output power *	900 W	Form factor *	Rackmount
Waveform *	Sine	Rack capacity	3U
Input operation voltage (min) *	220 V	Product colour *	Black, Grey
Input operation voltage (max) *	240 V	Display type	LCD
Input frequency *	40/70 Hz	LED indicators	Status
Output operation voltage (min)	220 V	International Protection (IP) code	IP20
Output operation voltage (max)	240 V	Operational conditions	
Output frequency	50/60 Hz	Operating temperature (T-T)	0 - 40 °C
Surge energy rating	340 J	Storage temperature (T-T)	-20 - 50 °C
Crest factor	3:1	Operating relative humidity (H-H)	0 - 95%
Emergency Power Off (EPO)	✓	Storage relative humidity (H-H)	0 - 95%
Noise level	50 dB	Operating altitude	0 - 3000 m
Surge protection	✓	Non-operating altitude	0 - 15000 m
Audible alarm(s)	✓	Certificates	
Auto-restart	✓	Certification	CE, EAC, RCM, VDE
Ports & interfaces		Sustainability	
AC outlet types	C13 coupler	Sustainability certificates	Green Premium
Power plug	C14 coupler	Weight & dimensions	
AC outlets quantity	8 AC outlet(s)	Width	432 mm
USB port	✓	Depth	590 mm
Serial interface	✓	Height	128 mm
Serial interface type	RJ-45	Weight	26.7 kg
Serial ports quantity	1	Packaging data	
SmartSlot	✓	Package width	600 mm
Battery		Package depth	850 mm
Battery technology	Lithium-Ion (Li-Ion)	Package height	445 mm
Battery life (max)	10 year(s)	Package weight	37.4 kg
Battery recharge time	6 h	Logistics data	
Hot-swap battery	✓	Products per pallet	6 pc(s)
Automatic battery test	✓	Harmonized System (HS) code	85078000
		Other features	
		Output voltage	230 V



0731304346388



731304346388

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.