APC

APC Smart-UPS On-Line, 1500VA, Rackmount 3U, 230V, 8x C13 IEC outlets, Network Card, Extended runtime, W/ rail kit, W/ Lithium-ion external battery

Brand : APC

Product name : Smart-UPS On-Line, 1500VA, Rackmount 3U, 230V, 8x C13 IEC outlets, Network Card, Extended runtime, W/ rail kit, W/ Lithium-ion external battery

Product code: SRTL1500RMXLI-NC

Smart-UPS On-Line, 1500VA, Rackmount 3U, 230V, 8x C13 IEC outlets, Network Card, Extended runtime, W/ rail kit, W/ Lithium-ion external battery

APC Smart-UPS On-Line, 1500VA, Rackmount 3U, 230V, 8x C13 IEC outlets, Network Card, Extended runtime, W/ rail kit, W/ Lithium-ion external battery:

This APC Smart-UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. This 1500VA on-line 3U rackmount UPS provides pure sine wave power and extended runtime to support critical electronics during power disruptions. It comes with IEC 320 C14 input and 8x IEC 320 C13 outlets. The UPS has a preinstalled Network Management Card for UPS network-based monitoring and management. The UPS comes with PowerChute Network Shutdown that provides graceful shutdown of physical servers, virtual machines, and HCI clusters. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. The UPS has a 5-year warranty on the UPS and Lithium-ion battery.

Features

UPS topology *	Double-conversion (Online)
Output power capacity *	1.5 kVA
Output power *	1350 W
Waveform *	Sine
Input operation voltage (min) *	220 V
Input operation voltage (max) *	240 V
Input frequency *	40/70 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Surge energy rating	340 J
Crest factor	3:1
Emergency Power Off (EPO)	✔
Noise level	50 dB
Surge protection	✔
Audible alarm(s)	✔
Auto-restart	✔

Ports & interfaces

AC outlet types	C13 coupler
Power plug	C14 coupler
AC outlets quantity	8 AC outlet(s)
USB port	✔
Serial interface	✔
Serial interface type	RJ-45
Serial ports quantity	1
Ethernet LAN (RJ-45) ports	1
Cabling technology	10/100Base-T
SmartSlot	✔

Battery

Battery technology	Lithium-Ion (Li-Ion)
Battery life (max)	10 year(s)
Battery recharge time	6 h

Battery

Automatic battery test	✔
Cold start	✔

Design

Form factor *	Rackmount
Rack capacity	3U
Product colour *	Black, Grey
Display type	LCD
LED indicators	Status
International Protection (IP) code	IP20

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 50 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Certificates

Certification	CE, EAC, RCM, VDE

Sustainability

Sustainability certificates	Green Premium

Weight & dimensions

Width	432 mm
Depth	590 mm
Height	128 mm
Weight	25.7 kg

Packaging data

Package width	600 mm
Package depth	850 mm
Package height	445 mm
Package weight	37.4 kg

Battery			**Logistics data**	
Hot-swap battery	✔		Products per pallet	6 pc(s)
			Harmonized System (HS) code	85078000
			Other features	
			Output voltage	230 V

0731304346418

731304346418

8592978108717