



APC SRT3000XLI UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 3 kVA 2700 W 10 AC-pistorasia(a)

Tuotemerkki : APC


Tuotekoodi: SRT3000XLI

Tuotteen nimi : SRT3000XLI

APC SRT3000XLI. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 3 kVA, Lähtöteho: 2700 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: C20 liitin, Ulostulojen määrä: 10 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 505 VAH, Tyypillinen varmuuskopioaika täydellä kuormituksella: 4 min. Kotelo: Tower, Tuotteen väri: musta, Johdon pituus: 2,44 m. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH



Runtime Graph




| Features | | Design | |
|---------------------------------|----------------------------|------------------------------------|---|
| UPS topology * | Double-conversion (Online) | Form factor * | Tower |
| Output power capacity * | 3 kVA | Cable length | 2.44 m |
| Output power * | 2700 W | Product colour * | Black |
| Waveform * | Sine | Display type | LCD |
| Input operation voltage (min) * | 100 V | LED indicators | ✓ |
| Input operation voltage (max) * | 275 V | International Protection (IP) code | IP20 |
| Input frequency * | 40/70 Hz | | |
| Output operation voltage (min) | 220 V | | |
| Output operation voltage (max) | 240 V | | |
| Output frequency | 50/60 Hz | | |
| Output frequency regulation | 50/60 Hz | | |
| Surge energy rating | 340 J | | |
| Efficiency | 93.5% | | |
| Crest factor | 3:1 | | |
| Emergency Power Off (EPO) | ✓ | | |
| Noise level | 55 dB | | |
| Surge protection | ✓ | | |
| Audible alarm(s) | ✓ | | |
| Web-based management | ✓ | | |
| Auto-restart | ✓ | | |
| | | | |
| Ports & interfaces | | Operational conditions | |
| AC outlet types | C13 coupler, C19 coupler | Operating temperature (T-T) | 0 - 40 °C |
| Power plug | C20 coupler | Storage temperature (T-T) | -15 - 45 °C |
| AC outlets quantity | 10 AC outlet(s) | Operating relative humidity (H-H) | 0 - 95% |
| Number of output IEC jumpers | 2 | Storage relative humidity (H-H) | 0 - 95% |
| USB port | ✓ | Operating altitude | 0 - 3000 m |
| Serial interface | ✓ | Non-operating altitude | 0 - 15000 m |
| Serial interface type | RJ-45 | | |
| SmartSlot | ✓ | | |
| | | | |
| | | Certificates | |
| | | Compliance certificates | RoHS |
| | | Certification | CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH |
| | | Packaging content | |
| | | Rack mount kit | ✓ |
| | | Cables included | USB cable |
| | | Quick installation guide | ✓ |
| | | Sustainability | |
| | | Sustainability certificates | ENERGY STAR, Green Premium |
| | | Weight & dimensions | |
| | | Width | 85 mm |
| | | Depth | 635 mm |
| | | Height | 432 mm |
| | | Weight | 31.3 kg |

| Battery | | Packaging data | |
|----------------------------------|-------------------------|-------------------------------------|--|
| Battery technology | Sealed Lead Acid (VRLA) | Bracket | ✓ |
| Battery capacity | 505 VAh | Warranty card | ✓ |
| Number of batteries supported | 1 | Software CD | ✓ |
| Typical backup time at full load | 4 min | Package width | 599 mm |
| Typical backup time at half load | 11.8 min | Package depth | 871 mm |
| Battery life (max) | 5 year(s) | Package height | 246 mm |
| Battery recharge time | 3 h | Package weight | 36.7 kg |
| Hot-swap battery | ✓ | Logistics data | |
| Automatic battery test | ✓ | Harmonized System (HS) code | 85078000 |
| Cold start | ✓ | Total carbon footprint (kg of CO2e) | 5053.66 |
| | | Other features | |
| | | Output voltage | 230 V |
| | | Packaging content | Country-specific detachable power cord Removable support feet |



0731304317678



731304317678

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.