APC Smart-UPS On-Line UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 5 kVA 4500 W 10 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SRT5KRMXLI





Tuotteen nimi : Smart-UPS On-Line

APC Smart-UPS On-Line. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 5 kVA, Lähtöteho: 4500 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: Hardwire, Ulostulojen määrä: 10 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 845 VAH, Tyypillinen varmuuskopioaika täydellä kuormituksella: 4 min. Kotelo: Telineasennettava, Tuotteen väri: musta, Telineen kapasiteetti: 3U. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: REACH, CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE

Features		Battery	
UPS topology *	Double-conversion (Online)	Cold start	1
Output power capacity *	5 kVA	Replacement battery cartridge	APCRBC140
Output power * 4500 W Vaveform * Sine nput operation voltage (min) * 100 V		Design	
		Form factor *	Rackmount
Input operation voltage (max) *	275 V	Rack capacity	30
Input frequency *	40 - 70 Hz	Product colour *	Black
Output operation voltage (min)	220 V	Display type	LCD
Output operation voltage (max)	240 V	Operational conditions	
Output frequency regulation	50/60 Hz	Operating temperature (T-T)	0 - 40 °C
Surge energy rating	480 J	Storage temperature (T-T)	-15 - 45 °C
Efficiency	94.1%	Operating relative humidity (H-H)	0 - 95%
Crest factor	3:1	Storage relative humidity (H-H)	0 - 95%
Emergency Power Off (EPO)	<i>✓</i>	Operating altitude	0 - 3000 m
Output voltage Total Harmonic Distortion (THD)	3%	Non-operating altitude	0 - 15000 m
Noise level	55 dB	Certificates	
Surge protection	✓	Compliance certificates	RoHS
Audible alarm(s)	✓	Certification	REACH, CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM,
Auto-restart	✓		RCM, VDE
Ports & interfaces		Packaging content	
AC outlet types	C13 coupler, C19 coupler	Rack mount kit	✓
Power plug	Hardwire	Quick installation guide	 Image: A start of the start of
AC outlets quantity	10 AC outlet(s)	Sustainability	
Number of output IEC jumpers USB port	2	Sustainability certificates	ENERGY STAR
Serial interface	 ✓ 	Weight & dimensions	
Serial interface type	RJ-45	Width	432 mm
SmartSlot	1	Depth	719 mm
Battery		Height	130 mm
Battery technology	Sealed Lead Acid (VRLA)	Weight	54.4 kg
Battery capacity	845 VAh	Packaging data	
Typical backup time at full load	4 min	Temperature sensor	✓
Typical backup time at half load	11.8 min	Warranty card	✓
Battery life (max)	5 year(s)	Package width	610 mm
Battery recharge time	1.5 h	Package depth	960 mm
Hot-swap battery	✓	Package height	330 mm
Automatic battery test	✓	Package weight	66.9 kg

Logistics data

Products per pallet Harmonized System (HS) code Total carbon footprint (kg of CO2e) 8408.59

6 pc(s) 85078000

Other features

Packaging content

Web/SNMP Management Card





731304301196

0731304301196

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.