


## APC Smart-UPS On-Line UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 8 kVA 8000 W 10 AC-pistorasia(a)

Tuotemerkki : APC Tuotekoodi: SRT8KRMXLI

Tuotteen nimi: Smart-UPS On-Line







		P. H.	
Features		Battery	
UPS topology *	* 476 V 40 - 70 Hz 220 V \$\text{c}\) 240 V 50/60 Hz 480 J 1 94.8% 3:1	Cold start	✓
Output power capacity *		Design	
Output power * Waveform * Input operation voltage (min) * Input operation voltage (max) * Input frequency * Output operation voltage (min) Output operation voltage (max)		Form factor * Rack capacity Product colour * Display type LED indicators  Operational conditions	Rackmount/Tower 6U Black LCD Status
Output frequency regulation Surge energy rating Number of output phases Efficiency Crest factor Emergency Power Off (EPO) Output voltage Total Harmonic Distortion (THD) Noise level Surge protection		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates Compliance certificates  Certification	0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3000 m 0 - 15000 m RoHS REACH, CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM,
Audible alarm(s) Auto-restart	<b>/</b>	Packaging content	RCM, VDE
Ports & interfaces		Rack mount kit	<b>✓</b>
AC outlet types Power plug	C13 coupler, C19 coupler Hardwire 10 AC outlet(s) 3	Rack mount kit  Cables included  Quick installation guide	VUSB cable ✓
AC outlets quantity		Weight & dimensions	
Number of output IEC jumpers USB port Serial interface		Width Depth Height	715 mm 432 mm 263 mm

Ports & interfaces		Weight & dimensions	
Serial interface type SmartSlot	RJ-45 ✓	Weight  Packaging data	111.8 kg
Battery		Bracket	/
Battery technology Battery capacity Typical backup time at full load Typical backup time at half load Battery life (max) Battery recharge time Hot-swap battery	Sealed Lead Acid (VRLA)  Temperature sensor  1728 VAh  Warranty card  5.2 min  Software CD  14.5 min  Package width  Package depth  Package height  Package weight	Warranty card Software CD Package width Package depth Package height	600 mm 1000 mm 461 mm 130 kg
Automatic battery test	<b>,</b>	Products per pallet Harmonized System (HS) code Total carbon footprint (kg of CO2e) Other features Packaging content	1 pc(s) 85078000 18632.76 Web/SNMP Management Card





731304304296

0731304304296

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.