




APC Smart-UPS On-Line UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 10 kVA 10000 W 10 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SRT10KRMXLI

Tuotteen nimi : Smart-UPS On-Line

APC Smart-UPS On-Line. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 10 kVA, Lähtöteho: 10000 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: Hardwire, Ulostulojen määrä: 10 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 1805 VAH, Tyypillinen varmuuskopioaika täydellä kuormituksella: 3,8 min. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Telineen kapasiteetti: 6U. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE, REACH



Features		Design	
UPS topology *	Double-conversion (Online)	Form factor *	Rackmount/Tower
Output power capacity *	10 kVA	Rack capacity	6U
Output power *	10000 W	Product colour *	Black
Waveform *	Sine	Display type	LCD
Input operation voltage (min) *	100 V	LED indicators	✓
Input operation voltage (max) *	476 V	Operational conditions	
Input frequency *	40 - 70 Hz	Operating temperature (T-T)	0 - 40 °C
Output operation voltage (min)	220 V	Storage temperature (T-T)	-15 - 45 °C
Output operation voltage (max)	240 V	Operating relative humidity (H-H)	0 - 95%
Output frequency regulation	50/60 Hz	Storage relative humidity (H-H)	0 - 95%
Surge energy rating	480 J	Operating altitude	0 - 3000 m
Number of output phases	1	Non-operating altitude	0 - 15000 m
Efficiency	94.6%	Certificates	
Crest factor	3:1	Compliance certificates	RoHS
Emergency Power Off (EPO)	✓	Certification	CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE, REACH
Output voltage Total Harmonic Distortion (THD)	3%	Packaging content	
Noise level	55 dB	Rack mount kit	✓
Surge protection	✓	Cables included	USB cable
Audible alarm(s)	✓	Quick installation guide	✓
Auto-restart	✓	Sustainability	
Ports & interfaces		Sustainability certificates	ENERGY STAR
AC outlet types	C13 coupler, C19 coupler	Weight & dimensions	
Power plug	Hardwire	Width	432 mm
AC outlets quantity	10 AC outlet(s)	Depth	715 mm
Number of output IEC jumpers	3	Height	263 mm
USB port	✓		
Serial interface	✓		

Ports & interfaces		Weight & dimensions	
Serial interface type	RJ-45	Weight	111.8 kg
SmartSlot	✓	Packaging data	
Battery		Bracket	✓
Battery technology	Sealed Lead Acid (VRLA)	Temperature sensor	✓
Battery capacity	1805 VAh	Warranty card	✓
Typical backup time at full load	3.8 min	Software CD	✓
Typical backup time at half load	11.5 min	Package width	600 mm
Battery life (max)	5 year(s)	Package depth	1000 mm
Battery recharge time	3 h	Package height	461 mm
Hot-swap battery	✓	Package weight	130 kg
Automatic battery test	✓	Logistics data	
Cold start	✓	Harmonized System (HS) code	85078000
		Total carbon footprint (kg of CO2e)	22873.91
		Other features	
		Interface	RJ-45 10/100 Base-T
		Nominal output voltage	230 V
		Nominal input voltage	230 V
		Packaging content	Web/SNMP Management Card



0731304304265



731304304265

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.