



## APC Smart-UPS UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 2,2 kVA 1980 W 10 AC-pistorasia(a)



**Tuotemerkki :** APC

**Tuotekoodi:** SRT2200RMXLI

**Tuotteen nimi :** Smart-UPS

APC Smart-UPS. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 2,2 kVA, Lähtöteho: 1980 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: C20 liitin, Ulostulojen määrä: 10 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 367 VAH, Tyypillinen varmuuskopioaika täydellä kuormituksella: 3,9 min. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Telineen kapasiteetti: 2U. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH

Features		Design	
UPS topology *	Double-conversion (Online)	Form factor *	Rackmount/Tower
Output power capacity *	2.2 kVA	Rack capacity	2U
Output power *	1980 W	Cable length	2.44 m
Waveform *	Sine	Product colour *	Black
Input operation voltage (min) *	100 V	Display type	LCD
Input operation voltage (max) *	275 V	LED indicators	✓
Input frequency *	40/70 Hz	International Protection (IP) code	IP20
Output operation voltage (min)	220 V	<b>Operational conditions</b>	
Output operation voltage (max)	240 V	Operating temperature (T-T)	0 - 40 °C
Output frequency regulation	50/60 Hz	Storage temperature (T-T)	-20 - 50 °C
Surge energy rating	340 J	Operating relative humidity (H-H)	0 - 95%
Efficiency	92.2%	Storage relative humidity (H-H)	0 - 95%
Crest factor	3:1	Operating altitude	0 - 3000 m
Emergency Power Off (EPO)	✓	Non-operating altitude	0 - 15000 m
Noise level	55 dB	<b>Certificates</b>	
Surge protection	✓	Compliance certificates	RoHS
Audible alarm(s)	✓	Certification	CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH
Web-based management	✓	<b>Packaging content</b>	
Auto-restart	✓	Rack mount kit	✓
<b>Ports &amp; interfaces</b>		Cables included	USB cable
AC outlet types	C13 coupler, C19 coupler	Quick installation guide	✓
Power plug	C20 coupler	<b>Sustainability</b>	
AC outlets quantity	10 AC outlet(s)	Sustainability certificates	ENERGY STAR, Green Premium
Number of output IEC jumpers	2	<b>Weight &amp; dimensions</b>	
USB port	✓	Width	432 mm
Serial interface	✓	Depth	584 mm
Serial interface type	RJ-45	Height	85 mm
SmartSlot	✓	Weight	25 kg
<b>Battery</b>		<b>Packaging data</b>	
Battery technology	Sealed Lead Acid (VRLA)	Bracket	✓
Battery capacity	367 VAh	Software CD	✓
Number of batteries supported	1	Package width	599 mm
Typical backup time at full load	3.9 min	Package depth	810 mm
Typical backup time at half load	11.6 min	Package height	246 mm
Battery life (max)	5 year(s)	Package weight	34 kg
Battery recharge time	3 h	<b>Logistics data</b>	
Hot-swap battery	✓	Products per pallet	12 pc(s)
Automatic battery test	✓	Harmonized System (HS) code	85078000
Cold start	✓		

**Logistics data**

Total carbon footprint (kg of CO2e) 3656.4

**Other features**

Nominal output voltage 230 V

Nominal input voltage 230 V



0731304317623



731304317623

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.