



APC SRT2200RMXLI-NC UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 2,2 kVA 1980 W 12 AC-pistorasia(a)



Tuotemerkki : APC

Tuotekoodi: SRT2200RMXLI-NC

Tuotteen nimi : SRT2200RMXLI-NC

APC SRT2200RMXLI-NC. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 2,2 kVA, Lähtöteho: 1980 W. Pistorasian tyypit: C13 liitin, C19 liitin, Ulostulojen määrä: 12 AC-pistorasia(a), Sarjaliitännän tyyppi: RJ-45. Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 367 VAh, Akun kestoikä (maks.): 5 vuosi/vuosia. Kotelo: Telineasennettava, Tuotteen väri: musta, Telineen kapasiteetti: 2U. Vaatimustenmukaisuustodistukset: RoHS, Sertifointi: CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE

Features		Design	
UPS topology *	Double-conversion (Online)	Rack capacity	2U
Output power capacity *	2.2 kVA	Cable length	2.44 m
Output power *	1980 W	Product colour *	Black
Waveform *	Sine	Display type	LCD
Input operation voltage (min) *	160 V	LED indicators	✓
Input operation voltage (max) *	275 V	International Protection (IP) code	IP20
Input frequency *	40 - 70 Hz	Operational conditions	
Output operation voltage (min)	220 V	Operating temperature (T-T)	0 - 40 °C
Output operation voltage (max)	240 V	Storage temperature (T-T)	-20 - 50 °C
Surge energy rating	340 J	Operating relative humidity (H-H)	0 - 95%
Crest factor	3:1	Storage relative humidity (H-H)	0 - 95%
Emergency Power Off (EPO)	✓	Operating altitude	0 - 3000 m
Output voltage Total Harmonic Distortion (THD)	2%	Non-operating altitude	0 - 15000 m
Noise level	55 dB	Certificates	
Audible alarm(s)	✓	Compliance certificates	RoHS
Ports & interfaces		Certification	CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE
AC outlet types	C13 coupler, C19 coupler	Sustainability	
AC outlets quantity	12 AC outlet(s)	Sustainability certificates	ENERGY STAR, Green Premium
Number of output IEC jumpers	2	Weight & dimensions	
USB port	✓	Width	432 mm
Serial interface	✓	Depth	584 mm
Serial interface type	RJ-45	Height	85 mm
Ethernet LAN (RJ-45) ports	1	Weight	25 kg
SmartSlot	✓	Packaging data	
Battery		Package width	599 mm
Battery technology	Sealed Lead Acid (VRLA)	Package depth	810 mm
Battery capacity	367 VAh	Package height	246 mm
Number of batteries supported	1	Package weight	34 kg
Battery life (max)	5 year(s)	Logistics data	
Battery recharge time	3 h	Harmonized System (HS) code	85078000
Design		Total carbon footprint (kg of CO2e)	3656.79
Form factor *	Rackmount	Other features	
		Output voltage	230 V



0731304327561



731304327561

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-FEB-2025. Prints or copies of Information are only valid on the printed Publication date