



APC Smart-UPS On-Line SRT UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 3 kVA 2700 W



Tuotemerkki : APC

Tuotekoodi: SRT3000RMXLI-NC

Tuotteen nimi : Smart-UPS On-Line SRT



APC Smart-UPS On-Line SRT. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 3 kVA, Lähtöteho: 2700 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: C20 liitin, Sarjaliitännän tyyppi: RJ-45. Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 505 VAH, Tyypillinen varmuuskopioaika täydellä kuormituksella: 4 min. Kotelo: Telineasennettava, Tuotteen väri: musta, Telineen kapasiteetti: 2U. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: CE, VDE, RCM, EAC, IEC/EN 62040-1, IEC/EN 62040-2, UL-1778, FCC 15 A, CSA

Features		Battery	
UPS topology *	Double-conversion (Online)	Automatic battery test	✓
Output power capacity *	3 kVA	Cold start	✓
Output power *	2700 W		
Waveform *	Sine		
Input operation voltage (min) *	100 V		
Input operation voltage (max) *	275 V		
Input frequency *	40 - 70 Hz		
Output operation voltage (min)	220 V		
Output operation voltage (max)	240 V		
Output frequency	50/60 Hz		
Automatic Voltage Regulation (AVR)	✓		
Surge energy rating	340 J		
Efficiency	92%		
Crest factor	3:1		
Emergency Power Off (EPO)	✓		
Output voltage Total Harmonic Distortion (THD)	2%		
Noise level	55 dB		
Surge protection	✓		
Power protection features	Overload		
Audible alarm(s)	✓		
Audible alarm modes	Battery replacement		
Auto-restart	✓		
Ports & interfaces		Design	
AC outlet types	C13 coupler, C19 coupler	Form factor *	Rackmount
Power plug	C20 coupler	Rack capacity	2U
USB port	✓	Cable length	2.44 m
Serial interface	✓	Product colour *	Black
Serial interface type	RJ-45	Display type	LCD
SmartSlot	✓	LED indicators	Battery replacement
		International Protection (IP) code	IP20
Battery		Operational conditions	
Battery technology	Sealed Lead Acid (VRLA)	Operating temperature (T-T)	0 - 40 °C
Battery capacity	505 VAh	Storage temperature (T-T)	-15 - 45 °C
Typical backup time at full load	4 min	Operating relative humidity (H-H)	0 - 95%
Typical backup time at half load	11.8 min	Storage relative humidity (H-H)	0 - 95%
Battery life (max)	5 year(s)	Operating altitude	0 - 3000 m
Battery recharge time	3 h	Non-operating altitude	0 - 15000 m
Hot-swap battery	✓		
		Certificates	
		Compliance certificates	RoHS
		Certification	CE, VDE, RCM, EAC, IEC/EN 62040-1, IEC/EN 62040-2, UL-1778, FCC 15 A, CSA
		Packaging content	
		Quick installation guide	✓
		Sustainability	
		Sustainability certificates	Green Premium
		Weight & dimensions	
		Width	432 mm
		Depth	635 mm
		Height	85 mm
		Weight	31.3 kg
		Packaging data	
		Package width	599 mm
		Package depth	871 mm
		Package height	246 mm
		Package weight	39.3 kg
		Logistics data	
		Products per pallet	6 pc(s)

Logistics data

Harmonized System (HS) code	85078000
Total carbon footprint (kg of CO2e)	4988.41

Other features

Output voltage	230 V
----------------	-------



0731304327592



731304327592

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.