TP-Link Tapo C310 Kuutio IP-turvakamera Ulkona 2304 x 1296 pikseliä Seinä

Tuotemerkki : TP-Link

Tuoteperhe: Tapo

Tuotekoodi: TAPO C310



Tuotteen nimi : C310

TP-Link Tapo C310. Malli: IP-turvakamera, Tuettu sijoitus: Ulkona, Yhteysteknologia: Langallinen & langaton. Kiinnitystyyppi: Seinä, Tuotteen väri: Valkoinen, Kotelo: Kuutio. Näkökentän kulma: 104°. Optisen sensorin koko: 25,4 / 2,7 mm (1 / 2.7"). Kiinteä polttoväli: 3,89 mm

| Placement supported * Out Connectivity technology * W Day/night mode ✓ Certification CE Design ✓ Form factor * Cu Mounting type * W Product colour * W LED indicators Sy | E, NCC Gube Vall Vhite ystem Dust resistant, Rain proof | Network Wi-Fi standards Bluetooth * Storage Built-in HDD * Card reader integrated Compatible memory cards Maximum memory card size Ports & interfaces Ethernet LAN (RJ-45) ports | 802.11b, 802.11g, Wi-Fi 4 (802.11n) × MicroSD (TransFlash) 128 GB |
|--|---|---|--|
| Placement supported * Out Connectivity technology * W Day/night mode ✓ Certification CE Design ✓ Form factor * Cu Mounting type * W Product colour * W LED indicators Sy | Vired & Wireless E, NCC Ube Vall Vhite ystem Pust resistant, Rain proof | Bluetooth * Storage Built-in HDD * Card reader integrated Compatible memory cards Maximum memory card size Ports & interfaces Ethernet LAN (RJ-45) ports | × × MicroSD (TransFlash) 128 GB |
| Connectivity technology *WDay/night mode✓CertificationCEDesignCForm factor *CuMounting type *WProduct colour *WLED indicatorsSy | Vired & Wireless E, NCC Ube Vall Vhite ystem Dust resistant, Rain proof | Storage Built-in HDD * Card reader integrated Compatible memory cards Maximum memory card size Ports & interfaces Ethernet LAN (RJ-45) ports | × ✓ MicroSD (TransFlash) 128 GB |
| Day/night modeImage: CertificationCertificationCertificationDesignImage: CertificationForm factor *CutMounting type *WutProduct colour *WutLED indicatorsSystem | r E, NCC Jube Vall Vhite ystem Dust resistant, Rain proof | Built-in HDD * Card reader integrated Compatible memory cards Maximum memory card size Ports & interfaces Ethernet LAN (RJ-45) ports | ✔ MicroSD (TransFlash) 128 GB |
| CertificationCertificationDesignForm factor *CuMounting type *WProduct colour *WLED indicatorsSy | E, NCC Gube Vall Vhite ystem Dust resistant, Rain proof | Card reader integrated Compatible memory cards Maximum memory card size Ports & interfaces Ethernet LAN (RJ-45) ports | ✔ MicroSD (TransFlash) 128 GB |
| DesignForm factor *CuMounting type *WProduct colour *WLED indicatorsSy | ube Vall Vhite ystem Just resistant, Rain proof | Compatible memory cards Maximum memory card size Ports & interfaces Ethernet LAN (RJ-45) ports | MicroSD (TransFlash) 128 GB |
| Form factor * Cu Mounting type * W Product colour * W LED indicators Sy | Vall Vhite ystem bust resistant, Rain proof | Maximum memory card size Ports & interfaces Ethernet LAN (RJ-45) ports | 128 GB |
| Mounting type *WProduct colour *WLED indicatorsSy | Vall Vhite ystem bust resistant, Rain proof | Ports & interfaces Ethernet LAN (RJ-45) ports | |
| Product colour * W LED indicators Sy | vhite ystem Just resistant, Rain proof | Ethernet LAN (RJ-45) ports | 1 |
| LED indicators Sy | ystem Just resistant, Rain proof | | 1 |
| · · · · · · · · · · · · · · · · · · · | oust resistant, Rain proof | DC in lock | |
| Protection realures Du | • | DC-in jack | 1 |
| | P66 | Security | |
| Weatherproof 🗸 | , | Video motion detection | 1 |
| Camera | | | 128-bit AES, SSL/TLS, WPA, WPA2- |
| Camera pan control X | , | Security algorithms | PSK |
| Camera tilt control | | Management features | |
| | 04° | Reset button | 1 |
| Image sensor | | Power | |
| Number of sensors 1 | | Power source type * | AC, DC |
| | 5.4 / 2.7 mm (1 / 2.7") | AC input voltage | AC, DC 100 - 240 V |
| | 3. , , 2., , , , , , , , , , , , , , , , | AC input frequency | 50 - 60 Hz |
| Lens system Number of lenses * 1 | | DC output voltage | 9 |
| Number of lenses *1Maximum aperture number2.1 | | DC output current | 0.6 A |
| | .89 mm | Operational conditions | |
| Night vision | | Operating temperature (T-T) | 0 - 40 °C |
| - | | Storage temperature (T-T) | -40 - 70 °C |
| Night vision * | 0 m | Operating relative humidity (H-H) | 10 - 90% |
| Night vision distance30LED typeIR | | Storage relative humidity (H-H) | 5 - 90% |
| 7 I ² = | 50 nm | System requirements | |
| Video | | | Android 4.4, Android 5.0, Android |
| | 304 x 1296 pixels | 1 | 5.1, Android 6.0, Android 7.0, Android 7.1, Android 7.1.2, Android |
| | MP | Mobile operating systems supported | 8.0, Android 9.0, iOS 10.0, iOS 11.0, |
| | .264 | | iOS 11.4, iOS 12, iOS 13, iOS 9.0, iOS 9.1, iOS 9.2, iOS 9.3 |
| Frame rate 15 | 5 fps | Weight & dimensions | |
| Video streaming | | Width | 142.3 mm |
| | | wiuti | 142.3 |

| Audio | | Weight & dimensions | |
|-------------------------------------|---|--------------------------------|----------------------|
| Built-in speaker(s) Audio system | ✓ 2-way | Depth Height | 103.4 mm 64.3 mm |
| Built-in microphone | Image: A set of the set of the | Packaging data | |
| Network | | Package width Package depth | 189.5 mm 201.5 mm |
| Ethernet LAN * | × IEEE 802.11b, IEEE 802.11g, IEEE 802.11n | Package height | 92.5 mm |
| Networking standards | | Package weight | 420 g |
| Wi-Fi * | ✓ | Packaging content | |
| | | Number of cameras * | 1 |
| | | Logistics data | |

Harmonized System (HS) code

85258900







Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.