

Chieftec PowerUp GPX-750FC virtalähdeyksikkö 750 W 20+4 pin ATX ATX musta

Tuotemerkki : Chieftec


Tuoteperhe: PowerUp

Tuotekoodi: GPX-750FC

Tuotteen nimi : GPX-750FC



Chieftec PowerUp GPX-750FC. Kokonaisteho: 750 W, AC-syöttöjännite: 100 - 240 V, AC-syöttötaajuus: 47 - 63 Hz. Emolevyn virtaliitin: 20+4 pin ATX, Emolevyn virtapiuhan pituus: 65 cm, SATA-virtakaapelin pituus: 500 mm. Tarkoitus: PC, Virransyöttöyksikön mitat: ATX, 80 PLUS certification: 80 PLUS Gold. Tuotteen väri: musta, Jäähdytyksen tyyppi: Aktiivinen, Tuulettimen halkaisija: 12 cm. Tuotteen leveys: 150 mm, Tuotteen syvyys: 140 mm, Tuotteen korkeus: 86 mm



Power		Ports & interfaces	
Total power *	750 W	PCI Express power cable length	65 cm
AC input voltage *	100 - 240 V	CPU power connector (4+4 pin)	✓
AC input frequency	47 - 63 Hz	ATX power connector (20+4 pin)	✓
Input current	10 A	Floppy drive power connector	1
Power Factor Correction (PFC) type	Active	Cabling type	Fully-Modular
Combined power (+3.3V)	110 W	Performance	
Combined power (+12V)	744 W	80 PLUS certification *	80 PLUS Gold
Combined power (+5V)	110 W	Purpose *	PC
Combined power (-12V)	3.6 W	Power supply unit (PSU) form factor *	ATX
Combined power (+5Vsb)	12.5 W	ATX version	2.53
Max output current (+3.3V)	20 A	Certification	80PLUS Gold
Max output current (+12V)	62 A	Design	
Max output current (+5V)	20 A	Product colour	Black
Max output current (-12V)	0.3 A	Cooling type	Active
Max output current (+5Vsb)	2.5 A	Fan diameter	12 cm
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage	Number of fans	1 fan(s)
Ports & interfaces		Fan location	Top
Motherboard power connector *	20+4 pin ATX	On/off switch	✓
Motherboard power cable length	65 cm	Weight & dimensions	
Number of SATA power connectors	9	Width	150 mm
SATA power cable length	500 mm	Depth	140 mm
Peripheral (Molex) power connectors (4-pin) *	3	Height	86 mm
Peripheral (Molex) power cable length	500 mm	Weight	2.3 kg
EPS power connector (4+4 pin)	✓	Packaging data	
PCI Express power connectors (6+2 pin)	4	Package weight	2.85 kg
		Package type	Box

Logistics data

Harmonized System (HS) code 84733020



0753263077196



753263077196

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.