Chieftec PowerUp GPX-850FC virtalähdeyksikkö 850 W 20+4 pin ATX ATX musta

Tuoteperhe: PowerUp

Tuotemerkki : Chieftec

Tuotekoodi: GPX-850FC

Tuotteen nimi : GPX-850FC


Chieftec PowerUp GPX-850FC. Kokonaisteho: 850 W, AC-syöttöjännite: 100 - 240 V, AC-syöttötaajuus: 47 - 63 Hz. Emolevyn virtaliitin: 20+4 pin ATX, Emolevyn virtapiuhan pituus: 65 cm, SATA-virtakaapelin pituus: 500,650,800 mm. Tarkoitus: PC, Virransyöttöyksikön mitat: ATX, 80 PLUS certification: 80 PLUS Gold. Tuotteen väri: musta, Tuulettimen halkaisija: 12 cm, Tuulettimien määrä: 1 tuuletin(ta). Sisältää johdot: AC, Prosessori (CPU), PCIe, Peripheral (Molex), SATA





Power		Ports & interfaces	
otal power *850 WC input voltage *100 - 240 VC input frequency47 - 63 Hznput current12 Aower Factor Correction (PFC) typeActiveActive130 W	CPU power connector (4+4 pin) CPU power cable length ATX power connector (20+4 pin) Floppy drive power connector Cabling type	✓ 80 cm ✓ 1 Fully-Modular	
Combined power (+3.3V) Combined power (+12V) Combined power (+5V) Combined power (-12V)	110 W 846 W 110 W 3.6 W 12.5 W 20 A 70.5 A 20 A	Performance 80 PLUS certification * Purpose *	80 PLUS Gold PC
Combined power (+5Vsb) Max output current (+3.3V) Max output current (+12V) Max output current (+5V)		Power supply unit (PSU) form factor * ATX version Certification	ATX 2.53 80PLUS Gold
Max output current (+5V) Max output current (+5Vsb) Power protection features	0.3 A 2.5 A Over current, Over power, Over voltage, Short circuit, Under voltage	Design Product colour Fan diameter	Black 12 cm
Ports & interfaces	5	Number of fans Fan location	1 fan(s) Top
Motherboard power connector * Motherboard power cable length Number of SATA power connectors SATA power cable length	20+4 pin ATX 65 cm 9 500,650,800 mm	On/off switch Packaging content Cables included	 AC, CPU, PCIe, Peripheral (Molex), SATA
Peripheral (Molex) power connectors (4-pin) *	3	Weight & dimensions Width	150 mm
Peripheral (Molex) power cable length PCI Express power connectors (6+2 pin) PCI Express power cable length	500,650,800,950 mm 6 65 cm	Width Depth Height Weight	140 mm 86 mm 2.4 kg

Packaging data			
Package weight	2.95 kg		
Package type	Box		
Logistics data			
Harmonized System (HS) code	84733020		





753263077202

0753263077202

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.