

D-Link DSL-3788 langaton reititin Gigabitti Ethernet Kaksitaajuus (2,4 GHz/5 GHz) musta

Tuotemerkki : D-Link

Tuotekoodi: DSL-3788/E

Tuotteen nimi : DSL-3788

D-Link DSL-3788. Wi-Fi-taajuus: Kaksitaajuus (2,4 GHz/5 GHz), Wi-Fi-standardi: Wi-Fi 5 (802.11ac), WLAN-tiedonsiirtonopeus (maks.): 866 Mbit/s. Ethernet LAN -käyttöliittymän tyyppi: Gigabitti Ethernet, Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s, Kaapelitekniikka: 10/100/1000Base-T(X). Tietoturva-algoritmit: WPA, WPA2. Tuotetyyppi: Pöytäreititin, Tuotteen väri: musta. Antennin muotoilu: Ulkoinen



WAN connection		Management features	
Ethernet WAN *	✓	Quality of Service (QoS) support	✓
DSL WAN *	✓	Reset button	✓
SIM card slot *	✗	WPS push button	✓
3G/4G USB modem compatibility *	✗	Security	
Wireless LAN features		Security algorithms	WPA, WPA2
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	Firewall	✓
Top Wi-Fi standard *	Wi-Fi 5 (802.11ac)	Design	
WLAN data transfer rate (max) *	866 Mbit/s	Product colour	Black
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)	Product type *	Tabletop router
WLAN data transfer rate (first band)	300 Mbit/s	Certificates	
WLAN data transfer rate (second band)	300 Mbit/s	Digital Living Network Alliance (DLNA) certified	✓
Network		Packaging content	
Ethernet LAN *	✓	AC adapter included	✓
Ethernet LAN interface type *	Gigabit Ethernet	Manual	✓
Ethernet LAN data rates	10,100,1000 Mbit/s	Antenna	
Cabling technology	10/100/1000Base-T(X)	Antenna design *	External
Networking standards	IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.1p, IEEE 802.3, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x	Antennas quantity	2
		Features	
		Firmware upgradeable	✓

Mobile network		Power	
3G	✘	Power source type *	DC
4G	✘	AC input voltage	100 - 240 V
DSL features		AC input frequency	50 - 60 Hz
ADSL	✔	Output voltage	12 V
ADSL2	✔	Output current	5 A
ADSL2+	✔	Operational conditions	
VDSL2	✔	Operating temperature (T-T)	0 - 45 °C
Internal modem	✔	Storage temperature (T-T)	-20 - 70 °C
Ports & interfaces		Operating relative humidity (H-H)	10 - 95%
Ethernet LAN (RJ-45) ports *	4	Weight & dimensions	
USB port *	✔	Width	210 mm
USB 2.0 ports quantity	1	Depth	30.8 mm
RJ-11 ports quantity	1	Height	150 mm
Memory card slot(s)	✘	Weight	277.4 g
DC-in jack	✔	Packaging data	
Management features		Number of products included	1 pc(s)
Web-based management	✔	Logistics data	
		Harmonized System (HS) code	85176990

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 09-MAR-2025. Prints or copies of Information are only valid on the printed Publication date