



D-Link DGS-1100-24PV2 verkkokytkin Hallittu L2 Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki musta

Tuotemerkki : D-Link

Tuotekoodi: DGS-1100-24PV2

Tuotteen nimi : DGS-1100-24PV2

D-Link DGS-1100-24PV2. Kytin tyyppi: Hallittu, Kytinkerros: L2. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 24. Täysin kaksipuolinen. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 48 Gbit/s. Verkkostandardit: IEEE 802.1AX, IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE.... Power over Ethernet -tuki. Telineasennus



Management features		Multicast features	
Switch type *	Managed	Multicast support	✓
Switch layer	L2	Design	
Quality of Service (QoS) support	✓	Rack mounting *	✓
Web-based management	✓	Product colour	Black
System event log	✓	LED indicators	✓
Ports & interfaces		Performance	
Basic switching RJ-45 Ethernet ports quantity *	24	Built-in processor	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Processor frequency	125 MHz
Network		Memory type	DRAM
Networking standards *	IEEE 802.1AX, IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Flash memory	16 MB
10G support *	✗	Noise level	0 dB
Copper ethernet cabling technology	10BASE-T, 10BASE-TX, 1000BASE-T	Fanless	✓
Port mirroring	✓	Mean time between failures (MTBF)	255003 h
Full duplex	✓	Power	
Flow control support	✓	AC input voltage	100 - 240 V
Link aggregation	✓	Power consumption (max)	19.5 W
Broadcast storm control	✓	Power over Ethernet (PoE)	
Rate limiting	✓	Power over Ethernet (PoE) *	✓
Auto MDI/MDI-X	✓	Power over Ethernet plus (PoE+) ports quantity	12
Spanning tree protocol	✓	Power over Ethernet (PoE) power per port	30 W
Head-of-line (HOL) blocking	✓	Total Power over Ethernet (PoE) budget	100 W
Auto-negotiation	✓	Operational conditions	
VLAN support	✓	Operating temperature (T-T)	-5 - 50 °C
Virtual LAN features	Port-based VLAN, Voice VLAN	Storage temperature (T-T)	-40 - 70 °C
		Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 2000 m

Network		Operational conditions	
Number of VLANs	128	Heat dissipation	107.5 BTU/h
Data transmission		Weight & dimensions	
Switching capacity *	48 Gbit/s	Width	280 mm
Forwarding rate	35.71 Mpps	Depth	230 mm
MAC address table *	8000 entries	Height	44 mm
Store-and-forward	✓	Weight	2.2 kg
Number of queues	4	Certificates	
Jumbo frames support	✓	Certification	EMI FCC A, CE A, VCCI A, C-Tick, BSMI, CCC cUL, CE LVD, CB, BSMI, CCC
Jumbo frames	9216	Logistics data	
Packet buffer memory	4.1 MB	Harmonized System (HS) code	85176990
Security			
DHCP features	DHCP client		
IGMP snooping	✓		
Security algorithms	SNMP, SSL/TLS		
Queue scheduling algorithms	SPQ, Weighted Round Robin (WRR)		



0790069451782



790069451782

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.