

Lenovo

Lenovo 40A90090EU kannettavien tietokoneiden telakka ja porttitoistin Langallinen USB 3.2 Gen 1 (3.1 Gen 1) Type-C musta

Tuotemerkki : Lenovo

Tuotekoodi: 40A90090EU

Tuotteen nimi : 40A90090EU

Lenovo 40A90090EU. Yhteysteknologia: Langallinen, Isäntäkoneen käyttöliittymä: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, USB-liitin: USB A-tyyppi, USB Type-C. Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s. Tuotteen väri: musta, Kaapelilukon aukkotyyppi: Kensington, Tuotemerkin yhteensopivuus: Lenovo. Virtalähteen malli: AC, Virtalähde: 90 W, Virtalähteen tyyppi: Ulkoinen. Tuotteen leveys: 171 mm, Tuotteen syvyys: 80 mm, Tuotteen korkeus: 32,5 mm



Ports & interfaces		Performance	
Connectivity technology *	Wired	Compatibility	A475, A275, E585, E485, E580, E480, E570,L380 Yoga, L380, L580, L480, Lenovo tablet 10, Miix 720, Miix 520, Miix 510, Miix 510, T580, T570, T480, T480s, T470, T470s, X1 Tablet Gen 3,X1 Tablet Gen 2, X1 Tablet Gen 1, X1 Carbon Gen 6, X1 Carbon Gen 5, X1 Yoga Gen 3, X1 Yoga Gen 2, X380 Yoga, X280, X270,Yoga 370, 13 Gen 2 Windows, 13 Gen 1 Windows, 11e Gen 5, Yoga 11e Gen 5,
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C		V330S-15ARR,V330-15ISK, V330-14IKB, V330-15IKB, ThinkPad 25
USB 2.0 ports quantity *	2		CB,CULUS,EAC,TUV Mark,FCC,ICES, DOC, NOM,KCC, RCM, BSMI, VCCI, CE, LoA
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	3		
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1		
VGA (D-Sub) ports quantity	1		
DisplayPorts quantity	2		
Combo headphone/mic port	✓		
USB connector type	USB Type-A, USB Type-C		
DC-in jack	✓		
Network		Certification	
Ethernet LAN *	✓		
Ethernet LAN (RJ-45) ports	1		
Ethernet LAN data rates	10,100,1000 Mbit/s		
Wake-on-LAN ready	✓		
10G support	✗		
Performance		Power	
Card reader integrated *	✗	Power source type	AC
Number of displays supported	2	Power supply	90 W
Cable lock slot	✓	Power supply type	External
Cable lock slot type	Kensington	Power plug type	Type C
Product colour *	Black	Compatible power plug types	EU
Brand compatibility	Lenovo	Operational conditions	
		Operating temperature (T-T)	-5 - 40 °C
		Operating relative humidity (H-H)	20 - 95%
		Weight & dimensions	
		Width	171 mm
		Depth	80 mm
		Height	32.5 mm
		Packaging content	
		Cables included	AC, USB Type-C
		AC adapter included	✓
		Logistics data	
		Harmonized System (HS) code	84733020



0190725798969



190725798969

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.