QNAP

QNAP TS-H973AX NAS Tower Ryzen Embedded V1500B 8 GB DDR4 0 TB QuTS hero musta

Tuotemerkki : QNAP Tuotekoodi: TS-H973AX-8G

Tuotteen nimi : TS-H973AX

QNAP TS-H973AX. Malli: NAS. Alustatyyppi: Tower. Laitteen luokka: Pienet & Keskikokoiset Yritykset. Suoritinperhe: Ryzen Embedded, Prosessorimalli: V1500B, Prosessorin taajuus: 2,2 GHz. Sisäinen muisti: 8 GB, Sisäisen muistin tyyppi: DDR4. Asennetun muistin kokonaiskapasiteetti: 0 TB. Käyttöjärjestelmä asennettu: QuTS hero





| | | _ | |
|------------------------------------|---|--|---|
| Storage | | Design | |
| Storage drive capacity * | 0 GB | Cable lock slot type | Kensington |
| | Serial ATA II, Serial ATA III, U.2 | Performance | |
| Storage drive sizes supported | 2.5,3.5" | Type * | NAS |
| RAID support * | ✓ | Device class * | Small & Medium Business |
| RAID levels | 0, 6, 1, 50, JBOD, 5, 60, 10 | Backup function * | ✓ |
| Online RAID expansion | ✓ | Backup features | Cloud, iSCSI LUN |
| RAID rebuild | ✓ | Buzzer | ✓ |
| Hot-swap drive bays | ✓ | Multilingual support | ✓ |
| Supported file systems | FAT32, HFS+, NTFS, ZFS, exFAT, ext3, ext4 | Noise level | 22.9 dB |
| Storage drives installed * | × | Third-party support | ✓ |
| Total installed storage capacity * | 0 TB | Snapshot | ✓ |
| Number of storage drives supported | g | Security algorithms | 256-bit AES, HTTPS, SSH |
| * | | Access Control List (ACL) | ✓ |
| Installed storage drive type * | × | Reset button | ✓ |
| Supported storage drive types * | HDD & SSD | On/off switch | ✓ |
| Disk roaming | ✓ | Built-in FTP server | ✓ |
| Processor Processor manufacturer * | AMD | Browser supported | Apple Safari, Google Chrome, Microsoft Internet Explorer, Mozilla Firefox |
| Processor generation | AMD Ryzen Embedded V1000 Series | System log | ✓ |
| • | • | Hot spare | ✓ |
| | | Password authentication | ✓ |
| · · | | Disk scan | ✓ |
| | | S.M.A.R.T. support | ✓ |
| | | Share folder | AFP. CIFS/SMB. FTP. WebDAV |
| • | 0.00 | USB copy function | ✓ |
| · | | | |
| , ,, | | | 0.701 |
| • • | | | • |
| • | SO-DIMM | Operating system version | 0.0.01 |
| Flash memory | 5000 MB | | |
| Network | | | |
| Ethernet LAN * | ✓ | | |
| Network | 5000 MB | Hot spare Password authentication Disk scan S.M.A.R.T. support | ✓ ✓ ✓ AFP, CIFS/SMB, FTP, WebD. |

| Network | | Software | |
|---|-----------------------------------|--|--|
| Ethernet LAN data rates | 100,1000,2500,5000,10000 Mbit/s | | Windows 10, Windows 10 |
| Ethernet LAN data rate supported (max) Copper ethernet cabling technology | | x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows Windows 11 x64, Windows 7, Windows 7 Enterprise, Windows Enterprise x64, Windows 7 Home Rasic Windows 7 Home Rasic x6 | Windows 10 Enterprise x64, Windows 10 Home, Windows 10 |
| DHCP client DHCP server | ✓ ✓ | | Windows 10 Pro, Windows 10 Pro |
| Jumbo frames support | √ | | x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 7. |
| iSCSI support | · | | Windows 7 Enterprise, Windows 7 |
| Wake-on-LAN ready | · ✓ | | Basic, Windows 7 Home Basic x64, |
| Supported network protocols | IPv4, IPv6 | supported | Windows 7 Home Premium, Windows 7 Home Premium x64. |
| Link aggregation | ✓ | Windows 7 Professional, Window Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 | Windows 7 Professional, Windows 7 |
| Load balancing system | ✓ | | Professional x64, Windows 7 Starter, Windows 7 Starter x64, |
| Dynamic DNS (DDNS) | ✓ | | Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, |
| Ports & interfaces | | | Windows 8, Windows 8 Enterprise, |
| USB port * | ✓ | | Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity | 3 | 8 x64 | 8 x64 CentOS 7.0, SuSE Linux 12.0, SuSE |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity | 1 | Linux 12.3, SuSE Linux 15, Ubur 14.04, Ubuntu 14.10, Ubuntu 15.10, Ubuntu 16.04, Ubuntu 15.10, Ubuntu 16.04, | Linux 12.3, SuSE Linux 15, Ubuntu |
| Ethernet LAN (RJ-45) ports * | 3 | | Ubuntu 15.10, Ubuntu 16.04, |
| Concurrent connections | 2000 | | Ubuntu 16.10, Ubuntu 17.10, Ubuntu 18.04 LTS, Ubuntu 20.04 |
| Design | | | LTS |
| Chassis type * | Tower | | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 |
| Cooling type * | Active | | Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X |
| Product colour Number of fans | Black 1 fan(s) | Mac operating systems supported | 10.15 Catalina, Mac OS X 10.15.3 |
| Fan diameter | 14 cm | | Catalina, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X |
| Drive bay locking | ✓ | | 10.9 Mavericks, Mac OS X 11.0 Big Sur |
| LED indicators | HDD, LAN, Power, SSD, Status, USB | | |
| | ,,,,, | | Windows Server 2003, Windows |
| Cable lock slot | ✓ | Server operating systems supported | Server 2008 R2, Windows Server |
| | | Server operating systems supported Other operating systems supported | Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows |
| | | | Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, |
| | | Other operating systems supported | Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, |
| | | Other operating systems supported Power Power supply location Power supply unit (PSU) capacity | Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11 External 120 W |
| | | Other operating systems supported Power Power supply location Power supply unit (PSU) capacity Number of power supply units | Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11 External 120 W 1 |
| | | Other operating systems supported Power Power supply location Power supply unit (PSU) capacity | Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11 External 120 W |
| | | Other operating systems supported Power Power supply location Power supply unit (PSU) capacity Number of power supply units Power consumption (typical) | Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11 External 120 W 1 55.41 W |
| | | Other operating systems supported Power Power supply location Power supply unit (PSU) capacity Number of power supply units Power consumption (typical) Power consumption (HDD standby) | Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11 External 120 W 1 55.41 W 41.2 W |
| | | Other operating systems supported Power Power supply location Power supply unit (PSU) capacity Number of power supply units Power consumption (typical) Power consumption (HDD standby) AC input voltage | Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11 External 120 W 1 55.41 W 41.2 W 100 - 240 V |
| | | Other operating systems supported Power Power supply location Power supply unit (PSU) capacity Number of power supply units Power consumption (typical) Power consumption (HDD standby) AC input voltage Fan voltage Weight & dimensions Width * | Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11 External 120 W 1 55.41 W 41.2 W 100 - 240 V 12 V |
| | | Other operating systems supported Power Power supply location Power supply unit (PSU) capacity Number of power supply units Power consumption (typical) Power consumption (HDD standby) AC input voltage Fan voltage Weight & dimensions Width * Depth * | Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11 External 120 W 1 |
| | | Other operating systems supported Power Power supply location Power supply unit (PSU) capacity Number of power supply units Power consumption (typical) Power consumption (HDD standby) AC input voltage Fan voltage Weight & dimensions Width * | Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11 External 120 W 1 55.41 W 41.2 W 100 - 240 V 12 V |
| | | Other operating systems supported Power Power supply location Power supply unit (PSU) capacity Number of power supply units Power consumption (typical) Power consumption (HDD standby) AC input voltage Fan voltage Weight & dimensions Width * Depth * Height * | Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11 External 120 W 1 |
| | | Other operating systems supported Power Power supply location Power supply unit (PSU) capacity Number of power supply units Power consumption (typical) Power consumption (HDD standby) AC input voltage Fan voltage Weight & dimensions Width * Depth * Height * Weight | Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11 External 120 W 1 55.41 W 41.2 W 100 - 240 V 12 V 224.6 mm 224.1 mm 182.7 mm 3.52 kg |
| | | Other operating systems supported Power Power supply location Power supply unit (PSU) capacity Number of power supply units Power consumption (typical) Power consumption (HDD standby) AC input voltage Fan voltage Weight & dimensions Width * Depth * Height * Weight Package weight | Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11 External 120 W 1 55.41 W 41.2 W 100 - 240 V 12 V 224.6 mm 224.1 mm 182.7 mm 3.52 kg |
| | | Other operating systems supported Power Power supply location Power supply unit (PSU) capacity Number of power supply units Power consumption (typical) Power consumption (HDD standby) AC input voltage Fan voltage Weight & dimensions Width * Depth * Height * Weight Package weight Packaging content External power adapter Cables included | Server 2008 R2, Windows Server 2012, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11 External 120 W 1 1 55.41 W 41.2 W 100 - 240 V 12 V 224.6 mm 224.1 mm 182.7 mm 3.52 kg 5.12 kg |
| | | Other operating systems supported Power Power supply location Power supply unit (PSU) capacity Number of power supply units Power consumption (typical) Power consumption (HDD standby) AC input voltage Fan voltage Weight & dimensions Width * Depth * Height * Weight Package weight Packaging content External power adapter Cables included Power cables quantity | Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11 External 120 W 1 |
| | | Other operating systems supported Power Power supply location Power supply unit (PSU) capacity Number of power supply units Power consumption (typical) Power consumption (HDD standby) AC input voltage Fan voltage Weight & dimensions Width * Depth * Height * Weight Package weight Packaging content External power adapter Cables included Power cables quantity Quick installation guide | Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11 External 120 W 1 |
| | | Other operating systems supported Power Power supply location Power supply unit (PSU) capacity Number of power supply units Power consumption (typical) Power consumption (HDD standby) AC input voltage Fan voltage Weight & dimensions Width * Depth * Height * Weight Package weight Packaging content External power adapter Cables included Power cables quantity | Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11 External 120 W 1 |

| Operational conditions | |
|-----------------------------------|-------------|
| Operating temperature (T-T) | 0 - 40 °C |
| Operating relative humidity (H-H) | 5 - 95% |
| Storage temperature (T-T) | -20 - 70 °C |
| Storage relative humidity (H-H) | 5 - 95% |
| Logistics data | |
| Harmonized System (HS) code | 84714100 |



4713213518649

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.