


BenQ MW809STH Lähiprojektori 3600 ANSI lumenia D-ILA WXGA (1280x800) 3D Valkoinen

Tuotemerkki : BenQ Tuotekoodi: 9H.JMF77.13E

Tuotteen nimi: MW809STH





Projector		Network	
Screen size compatibility * Projector brightness *	1778 - 3048 mm (70 - 120") 3600 ANSI lumens	Smart TV *	×
Projection technology *	D-ILA WXGA (1280x800) 22000:1 16:10	Ethernet LAN (DL 45) ports	1
Projector native resolution *		Ethernet LAN (RJ-45) ports	1
Contrast ratio (typical) *		Storage	
Native aspect ratio *		Card reader integrated *	×
Number of colours	1.07 billion colours	Features	
Horizontal scan range	15 - 102 kHz	Interactive *	✓
Vertical scan range Keystone correction, vertical	23 - 120 Hz -30 - 30°	Noise level (economic mode)	29 dB
Matrix size	1.65 cm (0.65")	On Screen Display (OSD)	✓
Matrix type	DMD		Arabic, Bulgarian, Simplified
Light source			Chinese, Traditional Chinese, Croatian, Czech, Danish, German,
Light source type *	Lamp		Dutch, English, Spanish, Finnish,
Service life of light source *	6000 h	On Screen Display (OSD) languages	French, Greek, Hindi, Hungarian, Indonesian, Italian, Japanese,
Service life of light source			Korean, Norwegian, Polish,
(economic mode)	10000 h		Portuguese, Romanian, Russian, Swedish, Thai, Turkish
Lamps quantity	1 lamp(s)	Number of OSD languages	28
Lens system		Noise level *	33 dB
Zoom capability	×	Multimedia	
Offset	105%	Built-in speaker(s) *	✓
Video		RMS rated power	10 W
Full HD *	×	Number of built-in speakers	1
3D*	✓	Design	
Supported 3D formats	Frame Sequential, Frame packing,	Market positioning *	Education
	Side by side, Top and bottom	Product type *	Short throw projector
Supported graphics resolutions	640 x 480 (VGA), 1920 x 1200 (WUXGA)	Product colour *	White
Supported video modes	480i, 480p, 576i, 576p, 720p, 1080i,	LED indicators	✓
Supported video modes	1080p	Cable lock slot	✓
Ports & interfaces		Cable lock slot type	Kensington
HDMI connector type	Full-size	Power	
S-Video inputs quantity	1	Power source *	AC
USB 2.0 ports quantity	1	Power consumption (typical) *	260 W
Mini-USB 2.0 ports quantity	1	Power consumption (standby) *	0.5 W
Audio (L/R) in *	1	AC input voltage	100 - 240 V
Headphone outputs Serial interface type *	1 RS-232	AC input frequency	50 / 60 Hz
Schai interface type	113-232		

ts & interfaces		Operational conditions		
C Audio in	✓	Operating temperature (T-T)		
GA (D-Sub) ports quantity *	(D-Sub) ports quantity * 3	Weight & dimensions		
I ports quantity * posite video in * port *	2 1 ×	Width Depth Height Weight *		
		Packaging content		
		Remote control included * Remote control type Manual		
		Logistics data		
		Harmonized System (HS) code		

