D-Link

D-Link DUB-E250 verkkokortti Ethernet 2500 Mbit/s

Tuotemerkki : D-Link Tuotekoodi: DUB-E250

Tuotteen nimi: DUB-E250

D-Link DUB-E250. Yhteysteknologia: Langallinen, Isäntäkoneen käyttöliittymä: USB Type-C, Käyttöliittymä: Ethernet. Tiedonsiirron enimmäisnopeus: 2500 Mbit/s. USB-virta. Tuotteen väri: Valkoinen






Ports & interfaces		Power	
Connectivity technology * Host interface * Interface *	Wired USB Type-C Ethernet 1 2.0/3.2 Gen 1 (3.1 Gen 1)	USB powered	✓
		System requirements	
Ethernet LAN (RJ-45) ports USB version			Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise,
Network			Windows 10 Enterprise x64, Windows 10 Home, Windows 10
Maximum data transfer rate *	2500 Mbit/s IEEE 802.1Q, IEEE 802.1p, IEEE	Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium, Windows 7 Home Premium x64,	Windows 10 IoT Enterprise,
Networking standards *	802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x		Enterprise, Windows 7 Enterprise
Ethernet LAN	✓		
Ethernet interface type	2.5 Gigabit Ethernet		
Ethernet LAN data rates	10,100,1000,2500 Mbit/s		Windows 7 Professional, Windows 7
Auto MDIX IEEE	✓		•
Full duplex	✓		
VLAN tagging	✓		·
Design			Windows 8 Enterprise x64, Windows
Product colour	White		8 Pro, Windows 8 Pro x64, Windows 8 x64
Internal *	×	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X	
Hot-Plug support	✓		
Plug and Play	✓		
LED indicators	✓		10.15 Catalina, Mac OS X 10.6 Snow
Certification	CE, FCC, IC		
Power			10.9 Mavericks
Power consumption	250 mA	Operational conditions	
		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	10 - 45 °C 10 - 70 °C 10 - 85%
		Storage relative humidity (H-H)	5 - 90%
		Weight & dimensions	
		Width	21.5 mm
		Depth	53 mm
		Height	15 mm
		Weight	28.5 g

Logistics data	
Harmonized System (HS) code	85176990
Other features	
Flow control support	✓
Cable length	0.16 m









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.