MSI MPG A750GF virtalähdeyksikkö 750 W 24-pin ATX ATX musta

Tuotemerkki: MSI Tuotekoodi: MPG A750GF

Tuotteen nimi: MPG A750GF

MSI MPG A750GF. Kokonaisteho: 750 W, AC-syöttöjännite: 100 - 240 V, AC-syöttötaajuus: 47 - 63 Hz. Emolevyn virtaliitin: 24-pin ATX, Emolevyn virtapiuhan pituus: 60 cm, SATA-virtakaapelin pituus: 950 mm. Tarkoitus: PC, Virransyöttöyksikön mitat: ATX, 80 PLUS certification: 80 PLUS Gold. Tuotteen väri: musta, Jäähdytyksen tyyppi: Aktiivinen, Tuulettimen halkaisija: 14 cm. Tuotteen leveys: 209 mm, Tuotteen syvyys: 287 mm, Tuotteen korkeus: 129 mm





Power		Ports & interfaces	
Total power *	750 W	EPS power connector (4+4 pin)	✓
AC input voltage *	100 - 240 V	PCI Express power connectors (6+2	6
AC input frequency	47 - 63 Hz	pin)	
Maximum input current (@110V)	10 A	PCI Express power cable length	50 cm
Maximum input current (@220V)	5 A	ATX Power connector (24-pin)	✓
Power Factor Correction (PFC) type	Active	Floppy disk drive connector	✓
Combined power (+3.3V)	120 W	Floppy disk drive cable length	110 cm
Combined power (+12V)	750 W	Cabling type	Fully-Modular
Combined power (+5V)	120 W	Performance	
Max output current (+3.3V)	22 A		00 PLUG C.14
Max output current (+12V)	25 A	80 PLUS certification *	80 PLUS Gold
Max output current (+12V1)	35 A	Purpose *	PC
Max output current (+12V2)	35 A	Power supply unit (PSU) form factor *	ATX
Max output current (+5V)	22 A	Country of origin	China
Max output current (-12V)	0.3 A	, ,	
Max output current (+5Vsb)	2.5 A	Design	
Efficiency	90%	Product colour	Black
Power protection features	Over current, Over power, Over	Cooling type	Active
	voltage, Short circuit, Under voltage	Fan diameter	14 cm
Ports & interfaces		Number of fans	1 fan(s)
Motherboard power connector *	24-pin ATX	Illumination	×
Motherboard power cable length	60 cm	On/off switch	✓
Number of SATA power connectors	8	Weight & dimensions	
SATA power cable length	950 mm	Width	209 mm
Peripheral (Molex) power connectors (4-pin) *	5	Depth	287 mm
EPS power connector (8-pin)	×	Height	129 mm
Lr 3 power connector (o-pin)	^	Weight	2.9 kg
		Packaging data	
		Package weight	2.98 kg
		Logistics data	
		Harmonized System (HS) code	84733020





824142225752

0824142225752

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.