

## QNAP QSW-M2108R-2C verkkokytkin Hallittu L2 2.5G Ethernet (100/1000/2500) Power over Ethernet -tuki musta



**Tuotemerkki :** QNAP

**Tuotekoodi:** QSW-M2108R-2C

**Tuotteen nimi :** QSW-M2108R-2C

QNAP QSW-M2108R-2C. Kytin tyyppi: Hallittu, Kytinkerros: L2. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: 2.5G Ethernet (100/1000/2500), Basic kytin RJ-45 Ethernet-porttien määrä: 8, Console-portti: RJ-45. Täysin kaksipuolinen. MAC-osoitetaulukko: 16000 entries, Kytintäkapasiteetti: 80 Gbit/s. Verkkostandardit: IEEE 802.1Q, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3az, IEEE.... Power over Ethernet -tuki. Telineasennus

Management features		Design	
Switch type *	Managed	Reset button	✓
Switch layer	L2	LED indicators	Activity, Link, Power, Speed, Status
Quality of Service (QoS) support	✓	Number of fans	1 fan(s)
Web-based management	✓	Electromagnetic compatibility	CLASS A
Ports & interfaces		Performance	
Basic switching RJ-45 Ethernet ports quantity *	8	Firmware upgradeable	✓
Basic switching RJ-45 Ethernet ports type *	2.5G Ethernet (100/1000/2500)	Fanless	✗
2.5G Ethernet (copper) ports quantity	8	Power	
Combo SFP ports quantity	2	Power source *	AC
Console port	RJ-45	Power supply included *	✓
Network		Number of power supply units	1
Networking standards *	IEEE 802.1Q, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	AC input voltage	100 - 240 V
		AC input frequency	50 - 60 Hz
10G support *	✓	Power consumption (max)	60 W
Full duplex	✓	Power over Ethernet (PoE)	
Auto-negotiation	✓	Power over Ethernet (PoE) *	✓
VLAN support	✓	Operational conditions	
Data transmission		Operating temperature (T-T)	0 - 40 °C
Switching capacity *	80 Gbit/s	Operating relative humidity (H-H)	5 - 95%
Throughput	40 Gbit/s	Weight & dimensions	
MAC address table *	16000 entries	Width	207 mm
Jumbo frames support	✓	Depth	199.5 mm
Jumbo frames	9000	Height	43.3 mm
Security		Weight	1.2 kg
DHCP features	DHCP client	Packaging content	
Access Control List (ACL)	✓	Quick start guide	✓
IGMP snooping	✓	Packaging data	
		Package weight	1.92 kg
		Certificates	
		Certification	CE, FCC, VCCI, BSMI

**Design**

Rack mounting \*



Product colour

Black

**Logistics data**

Harmonized System (HS) code

85176990



4713213518762

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-MAR-2025. Prints or copies of Information are only valid on the printed Publication date