TP-Link TL-WA1201 867 Mbit/s Valkoinen Power over Ethernet -tuki

Tuotemerkki : TP-Link

Tuotekoodi: TL-WA1201 V1

Tuotteen nimi : TL-WA1201

TP-Link TL-WA1201. 2,4 GHz, 5 GHz, Tiedonsiirron enimmäisnopeus: 867 Mbit/s. Tietoturva-algoritmit: 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK. Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s. Power over Ethernet -tuki. Tuotteen väri: Valkoinen

Features	
2.4 GHz *	✔
5 GHz *	✔
6 GHz *	✘
Maximum data transfer rate *	867 Mbit/s
Maximum data transfer rate (2.4 GHz)	300 Mbit/s
Maximum data transfer rate (5 GHz)	867 Mbit/s
Ethernet LAN data rates	10,100,1000 Mbit/s
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Cabling technology	10/100/1000Base-T(X)
MIMO	✔
MIMO type	Multi User MIMO
Fit AP mode features	Wireless distribution system (WDS)
Wi-Fi Multimedia (WMM)/(WME)	✔
Quality of Service (QoS) support	✔
Transmitting power (CE)	<20dBm(2.4GHz), <23dBm(5.15GHz~5.25GHz)
Transmitting power (FCC)	<30dBm(2.4GHz&5GHz)

Ports & interfaces	
WAN connection	Ethernet (RJ-45)
DC-in jack	✔

Power	
Power over Ethernet (PoE) *	✔
Output voltage	12 V
Output current	1.5 A

Design	
Placement *	Table
Product colour *	White
On/off switch	✔
Reset button	✔
WPS push button	✔
LED indicators	✔

Antenna	
Antenna type *	External
Antennas quantity	4

Performance	
Compatible operating systems	Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1, 10, MAC OS, NetWare, UNIX or Linux

Certificates	
Certification	CE, FCC, RoHS

Weight & dimensions	
Width	225 mm
Depth	145.5 mm
Height	37 mm

Features

Receiver sensitivity	5 GHz: , 11a 6 Mbps: -95 dBm, 11a 54 Mbps: -81 dBm , 11ac VHT20(MCS0): -94 dBm, 11ac VHT20(MCS8): -71 dBm , 11n HT40(MCS0): -91 dBm, 11n HT40(MCS7): -71 dBm , 11ac VHT80(MCS0): -88 dBm, 11ac VHT80(MCS9): -63 dBm , , 2.4 GHz: , 11g 54Mbps: -78 dBm , 11n HT20(MCS0): -92 dBm, 11n HT20(MCS7): -74 dBm , 11n HT40(MCS0): -88 dBm, 11n HT40(MCS7): -72 dBm

Security

Security algorithms *	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK
Service Set Identifier (SSID) features	Multiple SSIDs
Auto Wireless Distribution System (WDS)	✔
Access Control List (ACL)	✔

Protocols

DHCP server	✔
DHCP client	✔
Supported network protocols	IPv4, IPv6

Management features

Web-based management	✔
Firmware upgradeable	✔

Ports & interfaces

Ethernet LAN (RJ-45) ports *	1

Packaging data

Package width	400 mm
Package depth	255 mm
Package height	69 mm
Package weight	860 g
Package type	Box

Packaging content

Quantity per pack	1 pc(s)

Operational conditions

Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	5 - 90%

6935364052836