

ASUS RT-N12E C1 N300 langaton reititin Nopea Ethernet Yksi kaista (2,4 GHz) musta, Metallinen

Tuotemerkki : ASUS

Tuotekoodi: 90-IG29002M03-3PA0

Tuotteen nimi : RT-N12E C1 N300

ASUS RT-N12E C1 N300. Wi-Fi-taajuus: Yksi kaista (2,4 GHz), Wi-Fi-standardi: Wi-Fi 4 (802.11n), WLAN-tiedonsiirtonopeus (maks.): 300 Mbit/s. Ethernet LAN -käyttöliittymän tyyppi: Nopea Ethernet, Ethernet LAN -datanopeudet: 10,100 Mbit/s, Kaapelitekniikka: 10/100Base-T(X). Tietoturva-algoritmit: 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK, WPS. Tuotetyyppi: Pöytäreititin, Tuotteen väri: musta, Metallinen, LED-merkkivalot: LAN, Teho, WAN. Antennin muotoilu: Ulkoinen



WAN connection		Security	
Ethernet WAN *	✓	MAC address filtering	✓
DSL WAN *	✗	Network address translation (NAT)	✓
SIM card slot *	✗	Protocols	
3G/4G USB modem compatibility *	✗	DHCP client	✓
Wireless LAN features		Design	
Wi-Fi band *	Single-band (2.4 GHz)	Product colour	Black, Metallic
Top Wi-Fi standard *	Wi-Fi 4 (802.11n)	LED indicators	LAN, Power, WAN
WLAN data transfer rate (max) *	300 Mbit/s	Product type *	Tabletop router
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)	Antenna	
Network		Antenna design *	External
Ethernet LAN *	✓	Antennas quantity	2
Ethernet LAN interface type *	Fast Ethernet	Power	
Ethernet LAN data rates	10,100 Mbit/s	Power source type *	AC
Cabling technology	10/100Base-T(X)	AC input voltage	110 - 240 V
Networking standards	IEEE 802.11b, IEEE 802.11e, IEEE 802.11g, IEEE 802.11i, IEEE 802.11n, IEEE 802.3, IEEE 802.3u	AC input frequency	50 - 60 Hz
		Output current	0.5 A
Mobile network		Power over Ethernet (PoE)	✓
3G	✗	Operational conditions	
4G	✗	Operating temperature (T-T)	0 - 45 °C
Ports & interfaces		Storage temperature (T-T)	-20 - 70 °C
Ethernet LAN (RJ-45) ports *	4	Operating relative humidity (H-H)	10 - 90%
USB port *	✗	Storage relative humidity (H-H)	5 - 90%
Memory card slot(s)	✗	Weight & dimensions	
DC-in jack	✓	Width	124 mm
		Depth	168 mm

Management features		Weight & dimensions	
Web-based management	✓	Height	30 mm
Security		Weight	210 g
Security algorithms	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK, WPS	Logistics data	
Stateful Packet Inspection (SPI)	✓	Harmonized System (HS) code	85176990
Filtering	✓		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 29-DEC-2024. Prints or copies of Information are only valid on the printed Publication date