

QNAP QHora-301W langaton reititin 10 Gigabit Ethernet Kaksitaajuus (2,4 GHz/5 GHz) Valkoinen

Tuotemerkki : QNAP

Tuotekoodi: QHORA-301W

Tuotteen nimi : QHora-301W



QNAP QHora-301W. WAN -liitintyyppi: RJ-45. Wi-Fi-taajuus: Kaksitaajuus (2,4 GHz/5 GHz), Wi-Fi-standardi: Wi-Fi 6 (802.11ax), WLAN-tiedonsiirtonopeus (maks.): 2475 Mbit/s. Ethernet LAN -käyttöliittymän tyyppi: 10 Gigabit Ethernet, Ethernet LAN -datanopeudet: 1000,10000 Mbit/s, VPN-suoritusnopeus: 300 Mbit/s. Palomuurisuojaus: TCP, UDP, ICMP, TCP+UDP. Tuotetyyppi: Pöytäreititin, Tuotteen väri: Valkoinen

WAN connection		Design	
Ethernet WAN *	✓	On/off switch	✓
DSL WAN *	✗	Product type *	Tabletop router
SIM card slot *	✗	Certificates	
3G/4G USB modem compatibility *	✗	Certification	FCC, CE RED, RCM, NCC, BSMI, VCCI, IC, JATE, CCC, SRRC
WAN connection type	RJ-45	Packaging content	
Wireless LAN features		Cables included	AC, LAN (RJ-45)
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	Quick installation guide	✓
Top Wi-Fi standard *	Wi-Fi 6 (802.11ax)	Antenna	
WLAN data transfer rate (max) *	2475 Mbit/s	Antenna design *	Internal
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Antenna gain level (max)	5.2 dBi
Network		Antennas quantity	8
Ethernet LAN *	✓	Features	
Ethernet LAN interface type *	10 Gigabit Ethernet	Built-in processor	✓
Ethernet LAN data rates	1000,10000 Mbit/s	Processor manufacturer	Qualcomm
VPN throughput	300 Mbit/s	Processor model	Qualcomm IPQ8072A
Mobile network		Processor frequency	2200 MHz
3G	✗	Processor cores	4
4G	✗	Internal memory	1000 MB
5G	✗	Flash memory	4000 MB
Ports & interfaces		Number of concurrent sessions (max)	50000
Ethernet LAN (RJ-45) ports *	6	Power	
USB port *	✓	Power source type *	DC
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2	Output voltage	12 V
DC-in jack	✓	Power consumption (typical)	24 W
Management features		External power adapter	✓
Reset button	✓	Operational conditions	
WPS push button	✓	Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H)	5 - 95%

Security		Weight & dimensions	
Firewall	✓	Width	250 mm
Firewall security	TCP, UDP, ICMP, TCP+UDP	Depth	180 mm
Parental control	✓	Height	48 mm
Protocols		Weight	1.9 kg
Universal Plug and Play (UPnP)	✓	Packaging data	
Design		Package weight	2.2 kg
Product colour	White	Logistics data	
Wall mountable	✓	Harmonized System (HS) code	85176990



4713213517840

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-FEB-2025. Prints or copies of Information are only valid on the printed Publication date