ATEN CS19216-AT-G KVM-kytkin musta

Tuotemerkki : ATEN

Tuotekoodi: CS19216-AT-G

Tuotteen nimi : CS19216-AT-G


ATEN CS19216-AT-G. Näppäimistöportin liitin: USB, Hiiriportin liitin: USB, Videoportin tyyppi: DisplayPort. HD-tyyppi: 4K Ultra HD, Enimmäiserottelutarkkuus: 4096 x 2160 pikseliä, Videokaistanleveys: 60 Hz. Tuotteen väri: musta, Kotelon materiaali: Metalli. Voimanlähde: DC, Tulojännite: 12 V, Virrankulutus: 26,66 W. Tuotteen leveys: 432,4 mm, Tuotteen syvyys: 214,3 mm, Tuotteen korkeus: 44 mm



Ports & interfaces

Ports & interfaces		System requirements	
Number of computers controlled *	16	Windows operating systems	1
Keyboard port type *	USB	supported	
Mouse port type *	USB	Linux operating systems supported	✓
Video port type *	DisplayPort	Mac operating systems supported	1
DisplayPorts quantity	16	Operational conditions	
DisplayPort version	1.2	Operating temperature (T-T)	0 - 40 °C
USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity	16	Storage temperature (T-T)	-20 - 60 °C
Console ports *	3.5mm headphone, 3.5mm mic, DisplayPort, HDMI, USB A	Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 80% 0 - 80%
Console USB ports quantity	2	Weight & dimensions	
USB hub	 Image: A set of the set of the	Width	432.4 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-A	2	Depth	214.3 mm
hub ports quantity		Height	44 mm
USB connector type	USB Type-A, USB Type-B	Weight	4.18 kg
Audio connections		Packaging data	- J
Headphone outputs	17		
Number of microphone inputs	17	Package width	133 mm
DC-in jack	 Image: A set of the set of the	Package depth	499 mm
Performance		Package height Package weight	324 mm 5.33 kg
HD type *	4K Ultra HD	5 5	
Maximum resolution *	4096 x 2160 pixels	Packaging content	
Video bandwidth	60 Hz	Quick installation guide	v
Scan interval	1,5,255 s	Manual	1
HDCP		Logistics data	
Firmware upgradeable	1	Master (outer) case net weight	12.5 kg
Design		Harmonized System (HS) code	85176200
Product colour *	Black	Master (outer) case width	427 mm
Housing material	Metal	Master (outer) case length	519 mm
LED indicators	✓	Master (outer) case height	348 mm
Push button	1	Master (outer) case gross weight Products per master (outer) case	15.3 kg 3 pc(s)
Display		Troducts per master (vuter) tase	2 pc(3)
Built-in display *	×		

Power	
Power source	DC
Input voltage	12 V
Power consumption (typical)	26.66 W



4719264649264

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.