

BenQ LH890UST Lähietäisyysprojektori 4000 ANSI lumenia DLP 1080p (1920x1080) Valkoinen

Tuotemerkki : BenQ Tuotekoodi: 9H.JJD77.3HE

Tuotteen nimi: LH890UST

BenQ LH890UST. Projektorin kirkkaus: 4000 ANSI lumenia, Projektioteknologia: DLP, Projektorin oletusresoluutio: 1080p (1920x1080). Valonlähteen tyyppi: Laser, Valonlähteen käyttöikä: 20000 h.

Kiinteä polttoväli: 3,35 mm, Zoomin malli: Kiinteä, Heittosuhde: 0.23:1. Tuetut grafiikan

erottelutarkkuudet: 640 x 480 (VGA), 1920 x 1200 (WUXGA), Tuetut videomoodit: 1080p. Sarjaliitännän

tyyppi: RS-232, HDMI-versio: 1.4b





Projector		Storage	
Projector brightness *	4000 ANSI lumens	Card reader integrated *	×
Projection technology *	DLP	Features	
Projector native resolution * Contrast ratio (typical) *	1080p (1920x1080) 3000000:1	Interactive *	/
Native aspect ratio *	16:9	Interactive input supported	Interactive pen/Touch
Number of colours	1.07 billion colours	Noise level (economic mode)	32 dB
Keystone correction, horizontal	-20 - 20°	HDCP	✓
Keystone correction, vertical	-20 - 20°	Noise level *	35 dB
Matrix size	1.65 cm (0.65")	Certification	IP5X
Light source		Multimedia	
Light source type *	Laser	Built-in speaker(s) *	✓
Service life of light source *	20000 h	RMS rated power	10 W
Lens system		Number of built-in speakers	1
Fixed focal length	3.35 mm	TV tuner integrated	×
Zoom type	Fixed	Design	
Throw ratio	0.23:1	Market positioning *	Education
Offset	118.8%	Product type *	Ultra short throw projector
Video		Product colour *	White
Full HD *	✓	Placement	Ceiling, Desktop, Wall
Supported graphics resolutions	640 x 480 (VGA), 1920 x 1200 (WUXGA)	LED indicators	✓
Supported video modes	1080p	Power	
Ports & interfaces	·	Power source *	AC 358 W
HDMI version	1.4b	Power consumption (typical) * Power consumption (standby) *	0.5 W
S-Video inputs quantity	1.40	AC input voltage	100 - 240 V
USB 2.0 ports quantity	1	AC input frequency	50 - 60 Hz
Mini-USB 2.0 ports quantity	2	- 1	

Ports & interfaces		Operational conditions	
Headphone outputs	1	Operating temperature (T-T)	0 - 35 °C
Microphone in	RS-232 ty * 2 2 1	Weight & dimensions	
Serial interface type * VGA (D-Sub) ports quantity * HDMI ports quantity * Composite video in *		Width Depth Height Weight *	502.1 mm 399.3 mm 164.5 mm 9.06 kg
DVI port *	×	Packaging content	
Network		Remote control included *	√
Ethernet LAN * Ethernet LAN (RJ-45) ports	1	Remote control type Batteries included Cables included Mounting brackets included	IR ✓ AC, VGA ✓
		Logistics data	
		Harmonized System (HS) code	85286200

