



APC BVX900LI-GR uninterruptible power supply (UPS) Line-Interactive 0.9 kVA 480 W 2 AC outlet(s)

Brand : APC

Product code: BVX900LI-GR

Product name : BVX900LI-GR


900VA, 230V, AVR, 2x Schuko Sockets, Black

APC BVX900LI-GR. UPS topology: Line-Interactive, Output power capacity: 0.9 kVA, Output power: 480 W. AC outlet types: Type F, Power plug: Type F, AC outlets quantity: 2 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 9 Ah, Battery voltage: 12 V. Form factor: Compact, Product colour: Black, International Protection (IP) code: IP20. Certification: CB, CE, EN/IEC 62040-1, EN/IEC 62040-2



Features		Battery	
UPS topology *	Line-Interactive	Battery life (max)	2 year(s)
Output power capacity *	0.9 kVA	Battery recharge time	8 h
Output power *	480 W	Cold start	✓
Waveform *	Sine	Design	
Input operation voltage (min) *	170 V	Form factor *	Compact
Input operation voltage (max) *	280 V	Product colour *	Black
Input frequency *	50/60 Hz	LED indicators	✓
Output operation voltage (min)	230 V	International Protection (IP) code	IP20
Output operation voltage (max)	230 V	Operational conditions	
Output frequency	50/60 Hz	Operating temperature (T-T)	0 - 40 °C
Output frequency regulation	0.5 Hz	Storage temperature (T-T)	-15 - 40 °C
Output voltage regulation	10%	Operating relative humidity (H-H)	0 - 95%
Automatic Voltage Regulation (AVR)	✓	Operating altitude	0 - 3000 m
Surge energy rating	273 J	Non-operating altitude	0 - 3000 m
Response time	6 ms	Certificates	
Input power factor	0.53	Certification	CB, CE, EN/IEC 62040-1, EN/IEC 62040-2
Noise level	40 dB	Packaging content	
Surge protection	✓	Cables included	Input power cable
Audible alarm(s)	✓	Manual	✓
Audible alarm modes	Alarm when on battery, Battery replacement, Low battery alarm, Overload alarm	Weight & dimensions	
Ports & interfaces		Width	120 mm
AC outlet types	Type F	Depth	355 mm
Power plug	Type F	Height	160 mm
AC outlets quantity	2 AC outlet(s)		

Battery		Weight & dimensions	
Battery technology	Sealed Lead Acid (VRLA)	Weight	6 kg
Battery capacity	9 Ah	Packaging data	
Battery voltage	12 V	Package width	197 mm
		Package depth	430 mm
		Package height	250 mm
		Package weight	6.5 kg
		Logistics data	
		Harmonized System (HS) code	85078000



0731304404590



731304404590

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.