QNAP

QNAP QSW-M408-4C verkkokytkin Hallittu L2 Gigabit Ethernet (10/100/1000) Valkoinen

Tuotemerkki : QNAP

Tuotekoodi: QSW-M408-4C

Tuotteen nimi : QSW-M408-4C

QNAP QSW-M408-4C. Kytkin tyyppi: Hallittu, Kytkinkerros: L2. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 8, Console-portti: RJ-45. Täysin kaksipuolinen. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 96 Gbit/s. Verkkostandardit: IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE...

Management features

Switch type *	Managed
Switch layer	L2
Quality of Service (QoS) support	✔
Web-based management	✔

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity *	8
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)
Gigabit Ethernet (copper) ports quantity	8
Combo SFP ports quantity	4
Console port	RJ-45

Network

Networking standards *	IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support *	✔
Copper ethernet cabling technology	10BASE-T, 10GBASE-T, 1000BASE-LX, 1000BASE-SX, 1000BASE-T
Cable types supported	Cat5, Cat5e, Cat6
Full duplex	✔
Flow control support	✔
Spanning tree protocol	✔
Auto-negotiation	✔
VLAN support	✔
Virtual LAN features	Port-based VLAN, Private VLAN

Data transmission

Switching capacity *	96 Gbit/s
Throughput	48 Gbit/s
MAC address table *	16000 entries
Jumbo frames support	✔
Jumbo frames	9000

Design

Rack mounting *	✘
Stackable *	✘
Product colour	White
Reset button	✔
LED indicators	Activity, Link, Power, Speed, Status
Number of fans	1 fan(s)
Electromagnetic compatibility	CLASS A

Performance

Noise level	21 dB

Power

Power source *	AC
Power supply included *	✔
Number of power supply units	1
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (max)	31.46 W

Power over Ethernet (PoE)

Power over Ethernet (PoE) *	✘

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	5 - 95%

Weight & dimensions

Width	290 mm
Depth	127 mm
Height	42.5 mm
Weight	1.15 kg

Packaging content

Cables included	AC
Quick start guide	✔

Packaging data

Package weight	1.57 kg

Security		Certificates	
DHCP features	DHCP client	Certification	CE, FCC, VCCI, BSMI, CCC
Access Control List (ACL)	✔	**Logistics data**	
IGMP snooping	✔	Harmonized System (HS) code	85176990

4713213516713