

Epson EB-PU1007B Dataprojektori 7000 ANSI lumenia 3LCD WUXGA (1920x1200) musta

Tuotemerkki : Epson

Tuotekoodi: V11HA34840

Tuotteen nimi : EB-PU1007B



- Kompakti ja kevyt: Huomaamaton ja helpompi kuljettaa
- Linssien tuki: Tukee laajaa valikoimaa Epsonin vaihdettavia linssijä
- Parannettu muotoilu: Selkeä, yksinkertainen ja huomaamaton rakenne. Musta versio.
- Kuvanlaatu: 7 000 lumenia, 3LCD, WUXGA-tarkkuus ja 4K-kuvanparannus
- Edistykselliset asennustyökalut: Maksuttomia ohjelmistotyökaluja ja valinnainen ulkoinen kameramoduuli

EB-PU1007B

Epson EB-PU1007B. Projektorin kirkkaus: 7000 ANSI lumenia, Projektioteknologia: 3LCD, Projektorin oletusresoluutio: WUXGA (1920x1200). Valonlähteen tyyppi: Laser, Valonlähteen käyttöikä: 20000 h, Valonlähteen käyttöikä (säästötila): 30000 h. Polttovälialue: varies by lens, Zoomin malli: Auto, Heittosuhte: 0.35 - 10.11:1. Videon käsittely: 10 bittiä, Videon väritilat: Elokuvateatteri, Dynaaminen, Luonnollinen, Esitys, DICOM-tilannetila, Multi-projection, BT.709. Sarjaliitännän tyyppi: RS-232C



| Projector | | Design | |
|--|---|-----------------------------------|--|
| Projector brightness * | 7000 ANSI lumens | Market positioning * | Presentation |
| Projection technology * | 3LCD | Product type * | Large venue projector |
| Projector native resolution * | WUXGA (1920x1200) | Product colour * | Black |
| Contrast ratio (typical) * | 2000:1 | Placement | Ceiling, Desktop, Flying frame |
| Native aspect ratio * | 16:10 | Cable lock slot | ✓ |
| Number of colours | 1.07 billion colours | Cable lock slot type | Kensington |
| Projector brightness (economic mode) | 4900 ANSI lumens | Display | |
| Projector brightness (portrait mode) | 7000 ANSI lumens | Built-in display * | ✗ |
| Keystone correction, horizontal | -30 - 30° | Power | |
| Keystone correction, vertical | -45 - 45° | Power source * | AC |
| Matrix size | 1.93 cm (0.76") | Power consumption (typical) * | 431 W |
| Heat dissipation | 1465.4 BTU/h | Power consumption (standby) * | 0.5 W |
| Light source | | Power consumption (economy mode) | 366 W |
| Light source type * | Laser | AC input voltage | 100-240 V |
| Service life of light source * | 20000 h | AC input frequency | 50 - 60 Hz |
| Service life of light source (economic mode) | 30000 h | Software | |
| Lens system | | Software support | via: Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery |
| Focal length range | varies by lens | Operational conditions | |
| Zoom type | Auto | Storage temperature (T-T) | -10 - 60 °C |
| Throw ratio | 0.35 - 10.11:1 | Operating relative humidity (H-H) | 20 - 80% |
| Interchangeable lens | ✓ | Storage relative humidity (H-H) | 10 - 90% |
| Video | | Weight & dimensions | |
| Analog signal format system * | Not supported | Width | 545 mm |
| Full HD * | ✓ | Depth | 436 mm |
| 3D * | ✗ | Height | 189 mm |
| Video processing | 10 bit | Weight * | 16.3 kg |
| Video colour modes | Cinema, Dynamic, Natural, Presentation, DICOM simulation mode, Multi-projection, BT.709 | Package width | 570 mm |
| Ports & interfaces | | Package depth | 760 mm |
| HDBaseT port | ✓ | Package height | 270 mm |
| USB 2.0 ports quantity | 2 | Package weight | 21.5 kg |
| USB 2.0 Type-B ports quantity | 1 | | |

| Ports & interfaces | | Packaging content | |
|------------------------------|-------------|-----------------------------|--|
| Audio (L/R) in * | 1 | Remote control included * | ✓ |
| Serial interface type * | RS-232C | Batteries included | ✓ |
| VGA (D-Sub) ports quantity * | 1 | Cables included | AC |
| HDMI ports quantity * | 1 | Manual | ✓ |
| DVI port * | ✓ | Warranty card | ✓ |
| Network | | WLAN adapter included | ✓ |
| Ethernet LAN * | ✓ | Bundled software | Inhalt DIY-App, EasyMP Multi PC Projection, Epson Projektor Content Manager, Epson Projektor Management, Epson Projektor Professional Tool |
| Ethernet LAN (RJ-45) ports | 1 | | |
| Storage | | | |
| Card reader integrated * | ✗ | | |
| Features | | Logistics data | |
| Noise level (economic mode) | 29 dB | Quantity per pack | 1 pc(s) |
| HDCP | ✓ | Products per pallet | 14 pc(s) |
| Noise level * | 33 dB | Pallet gross weight | 0 g |
| Country of origin | Philippines | Products per pallet (UK) | 14 pc(s) |
| Password protection | ✓ | Pallet weight (UK) | 0 g |
| | | Harmonized System (HS) code | 85286200 |
| | | Other features | |
| | | Supported network protocols | HTTPS, IPv6, SNMP, ESC/VP.net, PJLink |



8715946697413

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-FEB-2025. Prints or copies of Information are only valid on the printed Publication date