

Epson EB-L635SU Vakioprojektori 6000 ANSI lumenia 3LCD WUXGA (1920x1200) musta

Tuotemerkki : Epson

Tuotekoodi: V11HA29140

Tuotteen nimi : EB-L635SU



EB-L635SU

Epson EB-L635SU. Projektorin kirkkaus: 6000 ANSI lumenia, Projektionteknologia: 3LCD, Projektorin oletusresoluutio: WUXGA (1920x1200). Valonlähteen tyyppi: Laser, Valonlähteen käyttöikä: 20000 h, Valonlähteen käyttöikä (säästötila): 30000 h. Tarkennus: Ohje, Kiinteä polttoväli: 11,8 mm, Aukkoalue (F-F): 1,7 - 1,7. Videon käsittely: 10 bittiä, Videon väritilat: Elokuvateatteri, Dynaaminen, Esitys, sRGB, DICOM-tilannetila, Multi-projection. Sarjaliitännän tyyppi: RS-232C, HDMI/liitäntätyyppi: Täysikokoinen

| Projector | | Features | |
|--|--|-----------------------------------|---|
| Smart projector * | ✗ | Noise level (economic mode) | 27 dB |
| Screen size compatibility * | 1270 - 5080 mm (50 - 200") | HDCP | ✓ |
| Projection distance (wide) | 0.9 - 3.5 m | Noise level * | 38 dB |
| Projector brightness * | 6000 ANSI lumens | Country of origin | Philippines |
| Projection technology * | 3LCD | Password protection | ✓ |
| Projector native resolution * | WUXGA (1920x1200) | Multimedia | |
| Contrast ratio (typical) * | 2500000:1 | Built-in speaker(s) * | ✓ |
| Native aspect ratio * | 16:10 | RMS rated power | 10 W |
| Number of colours | 1.07 billion colours | Number of built-in speakers | 1 |
| Projector brightness (economic mode) | 4200 ANSI lumens | Design | |
| Keystone correction, horizontal | -30 - 30° | Market positioning * | Presentation |
| Keystone correction, vertical | -30 - 30° | Product type * | Standard throw projector |
| Matrix size | 1.7 cm (0.67") | Product colour * | Black |
| Light source | | Placement | Ceiling, Desktop |
| Light source type * | Laser | Cable lock slot | ✓ |
| Service life of light source * | 20000 h | Cable lock slot type | Kensington |
| Service life of light source (economic mode) | 30000 h | Display | |
| Lens system | | Built-in display * | ✗ |
| Focus * | Manual | Power | |
| Fixed focal length | 11.8 mm | Power source * | AC |
| Aperture range (F-F) | 1.7 - 1.7 | Power consumption (typical) * | 345 W |
| Zoom capability | ✓ | Power consumption (standby) * | 0.3 W |
| Zoom type | Auto | Power consumption (economy mode) | 258 W |
| Zoom ratio | 1.35:1 | AC input voltage | 100-240 V |
| Throw ratio | 0.80:1 | AC input frequency | 50 - 60 Hz |
| Horizontal lens shift range | -20 - 20% | Software | |
| Vertical lens shift range | -50 - 50% | Software support | via: Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol |
| Video | | Operational conditions | |
| Full HD * | ✓ | Storage temperature (T-T) | -10 - 60 °C |
| Video processing | 10 bit | Operating relative humidity (H-H) | 20 - 80% |
| Video colour modes | Cinema, Dynamic, Presentation, sRGB, DICOM simulation mode, Multi-projection | Storage relative humidity (H-H) | 10 - 90% |

| Ports & interfaces | | Weight & dimensions | |
|-------------------------------|--|-----------------------------|---------------------------------------|
| HDMI connector type | Full-size | Width | 440 mm |
| HDBaseT port | ✓ | Depth | 334 mm |
| USB 2.0 ports quantity | 2 | Height | 136 mm |
| USB 2.0 Type-B ports quantity | 1 | Weight * | 8.4 kg |
| Serial interface type * | RS-232C | Package width | 540 mm |
| PC Audio in | ✓ | Package depth | 560 mm |
| PC Audio out | ✓ | Package height | 210 mm |
| VGA (D-Sub) ports quantity * | 2 | Package weight | 12.3 kg |
| HDMI ports quantity * | 3 | Packaging content | |
| DVI port * | ✗ | Remote control included * | ✓ |
| AC (power) in | ✓ | Batteries included | ✓ |
| Network | | Cables included | AC |
| Smart TV * | ✗ | Manual | ✓ |
| Ethernet LAN * | ✓ | Warranty card | ✓ |
| Ethernet LAN (RJ-45) ports | 1 | WLAN adapter included | ✓ |
| Wi-Fi * | ✓ | Logistics data | |
| Wi-Fi standards | 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac) | Quantity per pack | 1 pc(s) |
| Miracast | ✓ | Products per pallet | 14 pc(s) |
| Storage | | Pallet gross weight | 0 g |
| Card reader integrated * | ✗ | Products per pallet (UK) | 14 pc(s) |
| Features | | Pallet weight (UK) | 0 g |
| Interactive * | ✗ | Harmonized System (HS) code | 85286200 |
| | | Other features | |
| | | Supported network protocols | HTTPS, IPv6, SNMP, ESC/VP.net, PJLink |



8715946695372

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-FEB-2025. Prints or copies of Information are only valid on the printed Publication date