Chieftec BDK-750FC virtalähdeyksikkö 750 W 20+4 pin ATX ATX musta

Tuotemerkki : Chieftec Tuotekoodi: BDK-750FC

Tuotteen nimi: BDK-750FC

Chieftec BDK-750FC. Kokonaisteho: 750 W, AC-syöttöjännite: 100 - 240 V, AC-syöttötaajuus: 47 - 63 Hz. Emolevyn virtaliitin: 20+4 pin ATX, Emolevyn virtapiuhan pituus: 65 cm, SATA-virtakaapelin pituus: 150,500 mm. Tarkoitus: PC/palvelin, Virransyöttöyksikön mitat: ATX, 80 PLUS certification: 80 PLUS Bronze. Tuotteen väri: musta, Jäähdytyksen tyyppi: Aktiivinen, Tuulettimen halkaisija: 12 cm. Tuotteen leveys: 150 mm, Tuotteen syvyys: 140 mm, Tuotteen korkeus: 86 mm





Power		Ports & interfaces	
Total power * AC input voltage * AC input frequency	3.3V) 120 W 12V) 750 W 5V) 120 W 2V) 3.6 W 5Vsb) 12.5 W +3.3V) 20 A +12V) 62.5 A +5V) 20 A -12V) 0.3 A +5Vsb) 2.5 A Over current, Over voltage,	EPS power connector (4+4 pin) PCI Express power connectors (6+2 pin)	4
Input current Power factor		Floppy drive power connector Cabling type	1 Fully-Modular
Power Factor Correction (PFC) type Combined power (+3.3V) Combined power (+12V) Combined power (+5V) Combined power (-12V) Combined power (+5Vsb) Max output current (+3.3V) Max output current (+12V) Max output current (+5V) Max output current (-12V) Max output current (+5Vsb) Power protection features		Performance 80 PLUS certification * Purpose * Power supply unit (PSU) form factor * ATX version Bearing technology Certification Design Product colour Cooling type Fan diameter	80 PLUS Bronze PC/Server ATX 2.3 FDB EAC FCC CB Black Active 12 cm
rower protection leatures	Overheating, Overload, Under voltage	Number of fans	1 fan(s)
Ports & interfaces		Weight & dimensions	
Motherboard power connector * 20+4 pin ATX Motherboard power cable length 65 cm Number of SATA power connectors 6 SATA power cable length 150,500 mm	Width Depth Height Weight	150 mm 140 mm 86 mm 1.7 kg	
Peripheral (Molex) power connectors (4-pin) *	3	Packaging data	
Peripheral (Molex) power cable length	150,500 mm	Package weight Technical details	2.24 kg
		Sustainability compliance	/

Technical details				
Sustainability certificates	ErP			
Compliance certificates	CE, RoHS			
Logistics data				
Harmonized System (HS) code	84733020			





753263077431

0753263077431

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.