



ATEN VM6404HB-AT-G matriisikytkin Skaalautuva matriisikytkin Sisäänrakennettu näyttö

Tuotemerkki : ATEN

Tuotekoodi: VM6404HB-AT-G



Tuotteen nimi : VM6404HB-AT-G

ATEN VM6404HB-AT-G. Tuotetyyppi: Skaalautuva matriisikytkin, Tiedonsiirtonopeus: 18 Gbit/s, Maksimaalinen pikselikello: 600 MHz. Kotelon väri: musta, Kotelon materiaali: Metallia, Telineen kapasiteetti: 1U. Virrankulutus: 43,7 W, AC-syöttöjännite: 100-240 V, AC-syöttötaajuus: 50-60 Hz. Määrä per tuotepakkaus: 1 kpl, Tuotepakkauksen paino: 5,2 kg, Tuotepakkauksen pituus: 515 mm. Tuotteen leveys: 432,4 mm, Tuotteen syvyys: 262,3 mm, Tuotteen korkeus: 44 mm



Features		Operational conditions	
Product type *	Scaling matrix switcher	Operating temperature (T-T)	0 - 40 °C
Data transfer rate	18 Gbit/s	Storage temperature (T-T)	-20 - 60 °C
Maximum pixel clock	600 MHz	Operating relative humidity (H-H)	0 - 80%
Maximum resolution	4096 x 2160 pixels	Storage relative humidity (H-H)	0 - 80%
HDCP	✓	Heat dissipation	202 BTU/h
HDCP version	2.2	Heat dissipation (max)	205 BTU/h
3D	✓	Logistics data	
Extended display identification data (EDID)	✓	Products per master (outer) case	1 pc(s)
Supported resolutions	4096 x 2160, 3840 x 2160	Master (outer) case gross weight	5.2 kg
Design		Master (outer) case length	515 mm
Housing colour	Black	Master (outer) case width	338 mm
Housing material	Metal	Master (outer) case height	155 mm
Rack mounting	✓	Master (outer) case net weight	3.82 kg
Rack capacity	1U	Harmonized System (HS) code	85299097
Control type	Buttons	Weight & dimensions	
On/off switch	✓	Width	432.4 mm
LED indicators	✓	Depth	262.3 mm
Remote control included	✓	Height	44 mm
Display		Weight	3.82 kg
Built-in display *	✓	Package width	338 mm
Ports & interfaces		Package depth	515 mm
HDMI input ports quantity	4	Package height	155 mm
HDMI output ports quantity	4	Package weight	5.2 kg
Ethernet LAN (RJ-45) ports	1	Packaging content	
RS-232 ports	1	Cables included	AC
Remote (IR) input	1	Rack mount kit	✓
Power		Manual	✓
Power consumption (typical)	43.7 W	IR receiver included	✓
AC input voltage	100-240 V		
AC input frequency	50-60 Hz		
Input current	1 A		



4719264649608

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.