



## TP-Link Omada EAP610 WLAN-tukiasema 1775 Mbit/s Valkoinen Power over Ethernet -tuki

**Tuotemerkki :** TP-Link

**Tuoteperhe:** Omada

**Tuotekoodi:** EAP610

**Tuotteen nimi :** EAP610

TP-Link Omada EAP610. 2,4 GHz, 5 GHz, Tiedonsiirron enimmäisnopeus: 1775 Mbit/s. Tietoturva-algoritmit: WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3, WPA3-Enterprise. Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s. Power over Ethernet -tuki. Tuotteen väri: Valkoinen



Features		Management features	
2.4 GHz *	✓	Firmware upgradeable	✓
5 GHz *	✓	<b>Ports &amp; interfaces</b>	
6 GHz *	✗	Ethernet LAN (RJ-45) ports *	1
Maximum data transfer rate *	1775 Mbit/s	DC-in jack	✓
Maximum data transfer rate (2.4 GHz)	574 Mbit/s	<b>Power</b>	
Maximum data transfer rate (5 GHz)	1201 Mbit/s	Power over Ethernet (PoE) *	✓
Ethernet LAN data rates	10,100,1000 Mbit/s	Power over Ethernet (PoE) type supported	Passive PoE
Frequency band	2.4 - 5 GHz	DC voltage range	12 V
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	<b>Design</b>	
Cabling technology	10/100/1000Base-T(X)	Placement *	Ceiling, Wall
Automatic channel selection	✓	Product colour *	White
Automatic channel scanning	✓	Reset button	✓
MIMO	✓	LED indicators	✓
MIMO type	Multi User MIMO	<b>Antenna</b>	
Spread spectrum method	OFDMA	Antenna type *	Internal
Fit AP mode features	Mesh networking	<b>Certificates</b>	
VLAN support	✓	Certification	CE, FCC, RoHS
Rate limiting	✓	<b>Weight &amp; dimensions</b>	
Flow control support	✓	Width	160 mm
Band steering	✓	Depth	160 mm
Airtime Fairness (ATF)	✓	Height	33.6 mm
Quality of Service (QoS) support	✓		

Features		Packaging data	
Transmitting power (CE)	<20 dBm(2.4 GHz, EIRP); <23 dBm(5 GHz, EIRP)	Package type	Box
Transmitting power (FCC)	<25 dBm (2.4 GHz); <25 dBm (5 GHz)	Packaging content	
Security		Quantity per pack	1 pc(s)
Security algorithms *	WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3, WPA3-Enterprise	Mounting kit	✓
MAC address filtering	✓	Quick start guide	✓
Access Control List (ACL)	✓	Operational conditions	
Management features		Operating relative humidity (H-H)	10 - 90%
Web-based management	✓	Operating temperature (T-T)	0 - 40 °C
Syslog	✓	Storage temperature (T-T)	-40 - 70 °C
		Storage relative humidity (H-H)	5 - 90%



4897098682135



4897098683613



4897098687772

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.