



TP-Link TL-SG1218MPE Hallittu L2 Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki 1U musta

Tuotemerkki : TP-Link

Tuotekoodi: TL-SG1218MPE V1

Tuotteen nimi : TL-SG1218MPE



TP-Link TL-SG1218MPE. Kytin tyyppi: Hallittu, Kytinkerros: L2. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 16. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 36 Gbit/s. Verkkostandardit: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE.... Power over Ethernet -tuki. Telineasennus, Kotelo: 1U



Management features		Security	
Switch type *	Managed	Security algorithms	SNMP, SNMPv2, SNMPv3
Switch layer	L2	Loop protection	✓
Quality of Service (QoS) support	✓	Design	
Web-based management	✓	Rack mounting *	✓
Ports & interfaces		Form factor	1U
Basic switching RJ-45 Ethernet ports quantity *	16	Product colour	Black
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Number of fans	2 fan(s)
Gigabit Ethernet (copper) ports quantity	16	Power	
SFP module slots quantity	2	Power source *	AC
Network		Power supply included *	✓
Networking standards *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x	AC input voltage	100 - 240 V
10G support *	✗	AC input frequency	50 - 60 Hz
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	Power consumption (max)	217.22 W
Cable types supported	Cat3, Cat4, Cat5, Cat5e, Cat6	Power over Ethernet (PoE)	
Port mirroring	✓	Power over Ethernet (PoE) *	✓
Flow control support	✓	Power over Ethernet plus (PoE+) ports quantity	16
Link aggregation	✓	Total Power over Ethernet (PoE) budget	192 W
Broadcast storm control	✓	Operational conditions	
Rate limiting	✓	Operating temperature (T-T)	0 - 50 °C
Auto MDI/MDI-X	✓	Storage temperature (T-T)	-40 - 70 °C
Auto-negotiation	✓	Operating relative humidity (H-H)	10 - 90%
		Storage relative humidity (H-H)	5 - 90%
		Heat dissipation	741.15 BTU/h
		Weight & dimensions	

Network		Weight & dimensions	
VLAN support	✓	Width	440 mm
Virtual LAN features	Port-based VLAN	Depth	180 mm
Number of VLANs	32	Height	44 mm
Optical fiber		Packaging content	
Fiber ethernet cabling technology	1000BASE-X	Cables included	AC
Data transmission		User guide	✓
Switching capacity *	36 Gbit/s	Rack mount kit	✓
Forwarding rate	23.8 Mpps	Packaging data	
MAC address table *	8000 entries	Package width	250 mm
Store-and-forward	✓	Package depth	528 mm
Number of queues	4	Package height	80 mm
Jumbo frames support	✓	Package weight	2.91 kg
Jumbo frames	9000	Certificates	
Packet buffer memory	4.1 MB	Certification	CE, FCC, RoHS
Security		Logistics data	
IGMP snooping	✓	Harmonized System (HS) code	85176990



6935364086930



6935364086923



0845973086923



845973086923

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.