QNAP

QNAP QSW-M2108-2S verkkokytkin Hallittu L2 2.5G Ethernet (100/1000/2500) Harmaa

Tuotemerkki : QNAP

Tuotekoodi: QSW-M2108-2S

Tuotteen nimi : QSW-M2108-2S

QNAP QSW-M2108-2S. Kytkin tyyppi: Hallittu, Kytkinkerros: L2. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: 2.5G Ethernet (100/1000/2500), Basic kytkentä RJ-45 Ethernet-porttien määrä: 8, Console-portti: RJ-45. Täysin kaksipuolinen. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 80 Gbit/s. Verkkostandardit: IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE.... DC-syöttöjännite: 12 V

Management features	
Switch type *	Managed
Switch layer	L2
Quality of Service (QoS) support	✔
Web-based management	✔

Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity *	8
Basic switching RJ-45 Ethernet ports type *	2.5G Ethernet (100/1000/2500)
2.5G Ethernet (copper) ports quantity	8
SFP+ module slots quantity	2
Console port	RJ-45

Network	
Networking standards *	IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support *	✔
Copper ethernet cabling technology	100BASE-T, 1000BASE-T
Full duplex	✔
Flow control support	✔
Spanning tree protocol	✔
Auto-negotiation	✔
VLAN support	✔
Virtual LAN features	Tagged VLAN

Optical fiber	
Fiber ethernet cabling technology	1000BASE-LX, 1000BASE-SX

Data transmission	
Switching capacity *	80 Gbit/s
Throughput	40 Gbit/s
MAC address table *	16000 entries
Jumbo frames support	✔
Jumbo frames	9000

Security	
Access Control List (ACL)	✔
IGMP snooping	✔

Design	
Rack mounting *	✘
Stackable *	✘
Product colour	Grey
Reset button	✔
LED indicators	Activity, Link, Power, Speed, Status
Number of fans	1 fan(s)
Electromagnetic compatibility	CLASS A

Performance	
Firmware upgradeable	✔

Power	
Power source *	DC
Power supply included *	✔
DC input voltage	12 V
Power consumption (max)	23 W

Power over Ethernet (PoE)	
Power over Ethernet (PoE) *	✘

Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	5 - 95%

Weight & dimensions	
Width	290 mm
Depth	127 mm
Height	42.5 mm
Weight	1.12 kg

Packaging content	
Quick start guide	✔

Packaging data	
Package weight	1.52 kg

Security		Certificates	
DHCP features	DHCP client	Certification	CE, FCC, VCCI, BSMI
		Logistics data	
		Harmonized System (HS) code	85176990

4713213518373

0885022020393

885022020393