



ATEN VM0202HB-AT-G matriisikytkin AV-matriisikytkin

Tuotemerkki : ATEN

Tuotekoodi: VM0202HB-AT-G

Tuotteen nimi : VM0202HB-AT-G



ATEN VM0202HB-AT-G. Tuotetyyppi: AV-matriisikytkin, Tiedonsiirtonopeus: 18 Gbit/s, Maksimaalinen pikselikello: 600 MHz. Kotelon väri: musta, Kotelon materiaali: Metalli, Ohjaustyyppi: Painikkeet. USB-liitin: Micro-USB. Virrankulutus: 2,47 W. Määrä per tuotepakkaus: 5 kpl, Tuotepakkauksen paino: 5,25 kg, Tuotepakkauksen pituus: 325 mm

| Features | | Operational conditions | |
|---|--------------------------|-----------------------------------|-------------|
| Product type * | AV matrix switcher | Operating temperature (T-T) | 0 - 40 °C |
| Data transfer rate | 18 Gbit/s | Storage temperature (T-T) | -20 - 60 °C |
| Maximum pixel clock | 600 MHz | Operating relative humidity (H-H) | 0 - 80% |
| Maximum resolution | 4096 x 2160 pixels | Storage relative humidity (H-H) | 0 - 80% |
| HDCP | ✓ | Logistics data | |
| HDCP version | 2.2 | Products per master (outer) case | 5 pc(s) |
| 3D | ✓ | Master (outer) case gross weight | 5.25 kg |
| Firmware upgradeable | ✓ | Master (outer) case length | 325 mm |
| Extended display identification data (EDID) | ✓ | Master (outer) case width | 250 mm |
| Supported resolutions | 4096 x 2160, 3840 x 2160 | Master (outer) case height | 175 mm |
| Design | | Master (outer) case net weight | 4.25 kg |
| Housing colour | Black | Harmonized System (HS) code | 85299097 |
| Housing material | Metal | Weight & dimensions | |
| Rack mounting | ✓ | Width | 200 mm |
| Control type | Buttons | Depth | 76 mm |
| LED indicators | ✓ | Height | 42 mm |
| Remote control included | ✓ | Weight | 850 g |
| Display | | Package width | 59 mm |
| Built-in display * | ✗ | Package depth | 239 mm |
| Ports & interfaces | | Package height | 160 mm |
| HDMI input ports quantity | 2 | Package weight | 1 kg |
| HDMI output ports quantity | 2 | Packaging content | |
| USB connector type | Micro-USB | Rack mount kit | ✓ |
| USB ports quantity | 1 | Quick start guide | ✓ |
| RS-232 ports | 1 | AC adapter included | ✓ |
| Remote (IR) input | 1 | IR receiver included | ✓ |
| DC-in jack | ✓ | | |
| Power | | | |
| Power consumption (typical) | 2.47 W | | |



4710469340024

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.