Canon

Canon imageFORMULA ScanFront 400 ADF scanner 600 x 600 DPI A4 Black, White

Brand : Canon Product family: Product code: 1255C003

imageFORMULA

Product name: ScanFront 400

A4, ADF, CMOS CIS, RGB LED, 600 x 600DPI, 45ppm, Duplex, Ethernet,USB 2.0, touchscreen, 40W Canon imageFORMULA ScanFront 400. Maximum scan size: 216 x 356 mm, Optical scanning resolution: 600 x 600 DPI, ADF scan speed (b/w, A4): 45 ppm. Scanner type: ADF scanner, Product colour: Black, White, Display: TFT. Sensor type: CMOS CIS, Daily duty cycle (max): 6000 pages, Light source: RGB LED. Auto document feeder (ADF) input capacity: 60 sheets. Maximum ISO A-series paper size: A4, Scanning media types supported: Business Card, Plastic Card, Post Card(JPN), ISO A-series sizes (A0...A9): A4





Scanning		Paper handling	
	16 x 356 mm 00 x 600 DPI	Auto Document Feeder (ADF) media weight	
Colour scanning	✓	Maximum scan width	21.6 cm
Duplex scanning *	✓	Maximum scan length	35.6 cm
Greyscale levels	256	Ports & interfaces	
ADF scan speed (b/w, A4)	45 ppm	USB port *	✓
ADF scan speed (colour, A4)	45 ppm	USB version	2.0
Design		Standard interfaces	Ethernet, USB 2.0
Scanner type *	ADF scanner	Network	
Product colour *	Black, White	Ethernet LAN	✓
Display Display diagonal Display resolution	TFT 25.6 cm (10.1") 1024 x 600 pixels	Supported network protocols	TCP/IP (IPv4), DNS, DHCP, SMB, NTP, HTTP, FTP, SFTP, Secure sending (FTPS and SMTPS), WebDAV, LDAPS
Touchscreen	✓	Power	
Built-in display *	✓	Power supply type *	AC
Performance		Power consumption (typical)	40 W
Sensor type * CMOS CIS Light source RGB LED		Power consumption (off) AC input frequency Input voltage	0.5 W 50 - 60 Hz 100-240 V
Daily duty cycle (max) *	6000 pages	Weight & dimensions	
Scan to	E-mail, FTP, Fax, USB	Width	305 mm
Input capacity		Depth	282 mm
Auto document feeder (ADF) input		Height	230 mm
capacity	60 sheets	Weight	4.5 kg
Paper handling		Sustainability	
Scanning media types supported	Business Card, Plastic Card, Post Card(JPN) A4 A4 0.04 mm	Sustainability certificates	ENERGY STAR
, , , , , , , , , , , , , , , , , , ,		Operational conditions	
Maximum ISO A-series paper size *		Operating temperature (T-T)	10 - 32.5 °C
ISO A-series sizes (A0A9) Media thickness (min)		Operating relative humidity (H-H)	20 - 80%
		Other features	
		Compliance certificates	RoHS

Technical details	
Panel type	TFT
Logistics data	
Harmonized System (HS) code	84716070



4528472107110

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.