

iiyama TF1515MC-B2 infonäyttö 38,1 cm (15") LED 350 cd/m² XGA musta Kosketusnäyttö

Tuotemerkki : iiyama

Tuotekoodi: TF1515MC-B2

Tuotteen nimi : TF1515MC-B2

iiyama TF1515MC-B2. Näytön halkaisija: 38,1 cm (15"), Näytön teknologia: LED, Näytön erottelutarkkuus: 1024 x 768 pikseliä, Näytön kirkkaus: 350 cd/m², HD-tyyppi: XGA, Kosketusnäyttö. Tuotteen väri: musta



Display		Power	
Panel type	TN	Energy efficiency class (SDR)	E
Display diagonal *	38.1 cm (15")	Energy consumption (SDR) per 1000 hours	10 kWh
Display technology *	LED	Energy efficiency scale	A to G
Display resolution *	1024 x 768 pixels	Computer system	
Display brightness *	350 cd/m ²	Windows operating systems supported	✓
HD type *	XGA	Linux operating systems supported	✓
Touchscreen *	✓	Packaging data	
Touchscreen technology	Projected capacitive system	Package width	460 mm
Number of simultaneous touchpoints	10	Package depth	175 mm
Native aspect ratio	4:3	Package height	470 mm
Response time	8 ms	Package weight	4.6 kg
Contrast ratio (typical)	800:1	Packaging content	
Viewing angle, horizontal	160°	Cables included	AC, DisplayPort, HDMI, USB
Viewing angle, vertical	150°	Operational conditions	
Pixel pitch	0.297 x 0.297 mm	Operating temperature (T-T)	0 - 40 °C
Glass thickness	6 mm	Storage temperature (T-T)	-20 - 60 °C
Ports & interfaces		Certificates	
HDMI ports quantity *	1	Certification	CB, CE, TÜV-Bauart, EAC, cULus
DisplayPorts quantity *	1	Logistics data	
Design		Harmonized System (HS) code	85285210
Placement supported *	Horizontal/Vertical	Sustainability	
Product colour *	Black	European Product Registry for Energy Labelling (EPREL) code	378636
Screen shape	Flat	Features	
VESA mounting *	✓	Wall mountable	✓
Panel mounting interface	100 x 100 mm		
Performance			
On Screen Display (OSD)	✓		
Number of OSD languages	7		

Performance		Other features	
On Screen Display (OSD) languages	Simplified Chinese, German, English, Spanish, French, Italian, Japanese	Maximum refresh rate	75 Hz
HDCP	✓	Aspect ratio	4:3
International Protection (IP) code	IP65	Built-in microphone	✗
Power		LED indicators	✓
Power consumption (typical) *	16 W	Display viewable area (HxV)	304.1 x 228.1 mm
Power consumption (standby) *	1.2 W	Height (without stand)	41.5 mm
Power consumption (off)	1.2 W	Weight (without stand)	2.9 kg
		Depth (without stand)	291 mm
		Power supply type	AC/DC
		Built-in camera	✗
		Plug and Play	✓



4948570116751

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-MAR-2025. Prints or copies of Information are only valid on the printed Publication date